



SYMBOL LS3578-ER

RUGGED, CORDLESS SCANNER WITH INTEGRATED BLUETOOTH

SCAN BAR CODES OVER A WIDE RANGE OF DISTANCES

The LS3578-ER rugged, cordless scanner provides the greatest working range of any available rugged scanner, allowing employees to scan items from as close as .25 inches /.64cm to as far away as 45 feet /13.7 m. It also allows employees to quickly switch from reading bar codes on inventory to capturing smaller symbologies on bar code menus and pick lists. In the yard, warehouse, distribution center, manufacturing plant or retail store, the LS3578-ER offers superior performance and reliability as well as a user-friendly form factor that helps ensure comfortable use over long shifts. Plus, integrated Bluetooth provides reliable and secure wireless data transmission between the scanner and host, including Zebra's rugged VC5090 Vehicle-Fixed Mount Mobile Computer.

CORDLESS FREEDOM FOR IMPROVED PRODUCTIVITY

With no cord between the scanner and host, employees can move freely throughout their work environment, increasing productivity and efficiency while keeping supply chain inventory up to date at all times. Plus, having no cord reduces downtime from cable breakdowns – a common point of failure in handheld devices used in industrial facilities.

LOW TOTAL COST OF OWNERSHIP (TCO)

In addition to enhancing productivity, the LS3578-ER offers a low TCO. The industrial-strength construction maximizes the scanner's working life, and multiple on-board interfaces provide true plug-and-play simplicity with your host system today and tomorrow. Support for Remote Scanner Management (RSM) enables you to discover, provision and upgrade devices from a central remote location, dramatically reducing management time and costs. And since even the most rugged devices require a support plan, a full complement of Enterprise Mobility Services are available to help you protect your investment and maintain peak performance.

For more information on how the LS3578-ER can benefit your business, please visit us on the web at www.zebra.com/ls3578er or access our global contact directory at www.zebra.com/contact

FEATURES

Wide working range:
.25"/.64 cm to 45 ft./
13.7 m

Allows workers to scan items at varying distance without having to move, reducing fatigue and speeding task completion

Integrated Bluetooth® Class 2 v1.2 (Serial Port and HID Profiles with authentication and security)

Cordless scanning with secure wireless data transmission

Cordless scanning

Enables real-time bar code data collection unrestricted by a cable, reducing repairs from cable failure

Batch mode operation

Increases application design flexibility to better meet your specific needs

Ergonomic, rugged industrial design with-stands up to 50 drops to concrete from 6.5 ft. (2m) and 2,500 3 ft. (1m) tumbles (5,000 hits)

Ensures maximum reliability with less downtime resulting from accidental drops

IP65-rated seal (electronic enclosure)

Protects against water and dust for reliable performance in the harshest environments

Bright LED and beeper with adjustable volume

SPECIFICATIONS CHART

PHYSICAL CHARACTERISTICS		CRADLES	
Dimensions	7.34 in. L x 4.82 in. W x 2.93 in. D (18.65 cm H x 12.25 cm W x 7.43 cm D)	Power requirements	4.75 – 14 VDC (STB 3508 AND FLB 3508) 4.75 – 14 VDC (STB 3578 AND FLB 3578)
Weight (including LiON battery)	14.8 oz. (420 gm)	Not charging	STB 3508 AND FLB 3508 10 mA STB 3578 AND FLB 3578
Battery	2200 mAh Lithium Ion Battery		

Battery charge time	Fully charged (100%) in 3 hours
Color	Twilight Black and Yellow

PERFORMANCE CHARACTERISTICS	
Scanner type	Retrocollective
Light source	650 nm visible laser diode
Scan repetition	36 scans per second typical
Minimum element width	7.5 mil (0.191 mm)
Nominal working distance	See decode zone
Print contrast	25% minimum reflective difference
Roll (Tilt) ¹	+/- 10 degrees from normal
Pitch ²	+/- 65 degrees from normal
Skew (Yaw) ³	+/- 60 degrees from normal
Decode capability	UPC.EAN, UPC.EAN with Supplemental, GS1-128 (formerly UCC/EAN 128), JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, GS1DataBar (formerly RSS)
Interfaces supported	RS232, Keyboard Wedge, IBM 468X/469X, USB and Synapse

USER ENVIRONMENT

Operating Temp.	-4° to 122°F (-20° to 50°C)
Storage temperature	-40° to 140°F (-40° to 60°C)
Humidity	5% to 95% relative humidity, noncondensing
Sealing	Sealed to IP65 specifications
Drop specifications	Unit functions normally after 50 drops to concrete from 6.5 ft. (2m)
# of Cradle Insertions	250,000+ insertions
Ambient lighting tolerance	Tolerant to typical artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED4: 450 Ft Candles (4,842 Lux) Sunlight: 4,000 Ft Candles (43,040 Lux)
Electrostatic discharge	Conforms to 20 kV air discharge and 8 kV of contact discharge

	105 mA @5V 45 mA @9V
Fast rate charge	STB 3508 AND FLB 3508 915 mA @5V 660 mA @9V STB 3578 AND FLB 3578 915 mA @5V 660 mA @9V
Slow rate charge	STB 3508 AND FLB 3508 480 mA @5V 345 mA @9V STB 3578 AND FLB 3578 480 mA @5V 345 mA @9V

RADIO SPECIFICATION

Radio	Bluetooth, Class 2, Version 1.2, Serial port and HID Profiles
Frequency	2.402 to 2.480 GHz adaptive frequency hopping (co-existence with 802.11 wireless networks)
Data rate	720 kbps
Radio Range	Up to 300 ft. (100m) direct line of sight in open air; typical indoor cordless range is 100 ft. (33m), but will vary depending upon environment; see Bluetooth Radio Performance Technical Brief for more information

REGULATORY

Input transient protection	IEC 1000-4-(2,3,4,5,6,11)
EMI/RFI	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Japan VCCI/MITI/Dentori
Laser safety	IEC825-1 Class 2

WARRANTY

The LS3578-ER is warranted against defects in workmanship and materials for a period of 3 years (36 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty for details.

RECOMMENDED SERVICES

Support Services	Service from the Start - Bronze
1 - Roll (Tilt): Controlled by rotating the wrist clockwise or counterclockwise	
2 - Pitch: Controlled by dropping or raising the wrist	
3 - Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa	

Helps ensure that decode feedback is clearly visible and audible to users, even in noisy environments

Multi-point communication

Use up to three scanners with a single cradle, reducing capital expenditures and maintenance costs

Bright 650 nm laser aiming dot

Delivers clearly visible line for more accurate scanning

Supports GS1DataBar Symbologies (formerly RSS)

Ensures compatibility with emerging symbols to protect your hardware investment

Advanced data formatting

Eliminates costly modifications to the host software

Remote scanner management ready

Enables you to discover, provision and upgrade devices from a central remote location, reducing management time and costs

4 - LED lighting with high AC ripple content can impact scanning performance

DEPTH OF FIELD		
LABEL DENSITY	LS3578-ER	
Paper Label	English	Metric
Code 39 – 7.5 mil	0.25" – 20.00"	0.64 – 50.80 cm
Code 39 – 10 mil	2.00" – 32.00"	5.08 – 81.28 cm
Code 39 – 15 mil	3.00" – 69.00"	7.62 – 175.26 cm
Code 39 – 20 mil	3.00" – 94.00"	7.62 – 238.76 cm
Code 39 – 55 mil	15.00" – 180.00"	38.10 – 457.20 cm
REFLECTIVE LABEL		
Code 39 – 70 mil	Up to 30 ft.	Up to 9.27 m
Code 39 – 100 mil	Up to 45 ft.	Up to 13.72 m

For more detailed information, please see the Product Reference Guide in the Resource tab at www.zebra.com/ls3578er

CN410 CE



Part number: SS-LS3578. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES



800 729 0236
www.logiscenter.us



0241 9550 9225
www.logiscenter.de



01 82 88 44 70
www.logiscenter.fr



020 3318 8265
www.logiscenter.co.uk



0720 115814
www.logiscenter.at



02 58 80 583
www.logiscenter.be



911 433 048
www.logiscenter.com



02 4792 1697
www.logiscenter.it



308 800 842
www.logiscenter.pt

About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 60,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.



All Brands Technical Service


Our Brands




Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)