Planar URX75

75" 4K LCD Display

The Planar® UltraRes™ X URX75 is a TAA Compliant, 4K, HDR, professional 75" LCD display with on-board processing for viewing up to four content sources simultaneously. It features an OPS slot for additional connectivity, and a redundant power supply. With the optional Planar® Profile™ Mounting System it can achieve ADA compliance opening it to use in more environments ranging from meeting spaces to high impact digital signage and media rooms.



Specification:	Detail:
Product Name	URX75
Planar Part Number	998-2161-00
Display Resolution	Ultra HD (3840 x 2160)
Screen Size	75 in. (diagonal)
Aspect Ratio	16:9
Display Technology	Direct-lit LED LCD
Haze	44%
Surface Treatment	AG
Display Active Area	65.0" x 36.5" (1650.2mm x 928.3mm)
Viewing Angle (typ)	178°
Backlight	LED
Backlight life (1/2 brightness)	50,000 hrs (min)

Specification:	Detail:
Brightness (typ)	700 nits
Response Time (typ)	6.5 ms
Frame Rate	60Hz
Contrast Ratio (typ)	5000:1
Contrast Ratio - Dynamic	20,000:1
Pixel Pitch	0.4298 mm
Color Gamut	88% NTSC
HDR (High Dynamic Range)	HDR10
Display Color	>1 billion colors. Full 10 bit data path
External Connections	DisplayPort 1.2 in x 1, DisplayPort out, HDMI® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS x 1
Modes	3840x2160 @ 24/25/30/60Hz, 1920x1080 @ 24/25/30/50/60Hz, 480p, 576p, 720p @ 50/60 Hz, 1080i @ 50/60 Hz
Display Control	IR, RS-232, LAN, HDMI-CEC, Keypad, Web Browser Interface
Cabinet Dimensions (W x H x D)	66.3" x 37.9" x 3.7" (1685.0mm x 963.0mm x 92.9mm)
Dimensions including Wall Mount	66.3" x 37.9" x 3.8" (1685.0mm x 963.0mm x 95.9mm)
Orientation	Landscape/Portrait
Bezel Width	0.7" (16.5mm)
Display Edge to Active Area	0.7" (17.2mm)
Weight	145 lb (66 kg)
Audio Input	PC Line In
Audio Output	PC Line Out, S/PDIF
Speakers	10W x 2 built-in
Enclosure	Metal

Specification:	Detail:
Mounting	Planar Profile Mounting System or VESA: 400 x 400 mm
Fanless	Yes
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	180W (standby: <0.5W)
Operating Temperature	0° to +40°C (32° to 104°F) at up to 1500m, 0° to +35°C (32° to 95°F) at up to 3000m
Humidity	20 - 85% RH (non-condensing)
Options / Features	MediaPlex Plus Processing, Scheduling, Presets, Redundant power supply
Multi-Source Views	PiP, Dual, Triple, Quad
Approvals	FCC Class A, CE, cTUVus, RoHS
TAA Compliance	Yes
Security	No WiFi, no Android O/S, signed and encrypted firmware
Warranty	3 years Advance Exchange
Recommended Usage	Up to 24x7 operation
In the Box	URX75 display, US power cord, HDMI cable, IR sensor, remote control, lifting straps x2, QuickStart Guide
UPC	8 10689 00807 1
HDMI®	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Planar is a trademark of Planar Systems, Inc. All other trademarks and service marks are property of their holders. Copyright © 2025 Planar Systems, Inc. All rights reserved. This document may not be copied in any form without permission from Planar. Information in this document is subject to change without notice.