

MAGTEK®
SECURITY FROM THE INSIDE

mobile
payments

cDynamo

Secure Card Reader Authenticator

The cDynamo makes mobile payments easier than ever. It delivers a form fitted enclosure case with integrated secure card reader authenticator (SCRA) for iPad Mini, iPad Air and iPad Air 2 to keep them safe, while enabling merchants to accept mobile payments.

cDynamo offers the MagneSafe™ Security Architecture (MSA) combined with the power of iOS tablets (with Lightning interface). The MSA delivers open standards encryption with simple, yet proven DUKPT key management, immediate tokenization of card data, and MagnePrint® card authentication to maximize data protection and prevent the use of counterfeit cards. Mobile merchants can leverage the power of their iOS tablets without the worries of handling or storing sensitive card data at any time. Ideal for small to mid-size merchants, this powerful combination assures convenience and cost savings while ensuring transaction security from the moment the card is swiped all the way to authorization.



cDynamo SCRA

**Call a representative to learn more
562-546-6400**

secure devices

Other devices claim to encrypt data in the reader. The cDynamo encrypts the data inside the read head, closest to the magnetic stripe and offers additional security layers with immediate tokenization of card data and MagnePrint card authentication. This layered approach to security far exceeds the protection of encryption by itself, decreases the scope of PCI compliance, and reduces fraud.

The cDynamo is rugged and affordable to withstand real world use and performs to the high standards set by MagTek, the world's most prolific supplier of secure payment technology for over 40 years. The swipe path is optimized for a more reliable and stable one-swipe read.

The cDynamo features a 100mm VESA (Video Electronics Standards Association) mounting pattern that provides fixed mounting for greater security and convenience. This allows users to deploy the cDynamo in a variety of off the shelf semi-mobile or permanent mounts eliminating the need for expensive customization.

Charging the cDynamo and connected iPad is easy with the cDynamo's built-in, pass-through, micro-USB port that accommodates Apple certified USB cables and power bricks.

MagTek provides SDKs and APIs for easy development and integration to reduce time to market.

Product Compatibility

cDynamo Air 2 PN 21087007:	iPad Air 2, 6th gen
cDynamo Air PN 21087005:	iPad Air
cDynamo Mini PN 21087006:	iPad mini 3, iPad mini 2, iPad mini



Specifications

SECURE CARD READER AUTHENTICATOR (SCRA)

Three (3) tracks, bi-directional read
ISO 7810/7811, ANSI/ISO/AAMVA and custom formats
Card Speed: 6 to 60 ips (15 to 152 cm/s)
Protects card data per PCI DSS requirements
MagnePrint card authentication
Generates dynamic payment card data with each swipe
Device/host authentication
Unique, non-changeable serial number
Time bound session IDs
Triple DES open standards-based encryption
DUKPT key management
Immediate card data tokenization and masked data

MESSAGE FORMAT

ASCII

INTERFACE CONNECTOR

Lightning connection only

OPERATING SYSTEM

iOS 6 or newer

CONTROLS

The cDynamo has no user controls. Control, status and data functions are provided by the host interface.

The system requires software on the host device to direct the operation of the card reader through the application programming interface (API).

MOUNTING

VESA Mount = MIS-D 4" x 4" (100mm x 100mm)
Qty 4 - M4 screw threads

MECHANICAL

iPad mini
W 5.47 x L 9.71 x D 0.72 (inch)
WT: 1.5lb with iPad mini

iPad Air/2
W 6.85 x L 11.28 x D 0.72 (inch)
WT: 1.5lb with iPad Air/2

VOLTAGE/POWER/CHARGING

Current: 50mA max. 100% of its power IS from the iOS tablet. There is no power switch and no batteries are required. A Micro-USB is for charging the tablet only and cannot be used as an interface.

MF1 APPROVED DEVICE

ENVIRONMENTAL

TEMPERATURE

Operating: 0 °C to 35 °C (32 °F to 95 °F)
Storage: -20 °C to 45 °C (-4 °F to 113 °F)

HUMIDITY

Operating: 5% to 90% noncondensing
Storage: 5% to 90% noncondensing

ALTITUDE

Operating: 3000m (10,000 ft)



800 729 0236
www.logiscenter.us



0241 9550 9225
www.logiscenter.de



01 82 88 44 70
www.logiscenter.fr



020 3318 8265
www.logiscenter.co.uk



0720 115814
www.logiscenter.at



02 58 80 583
www.logiscenter.be



911 433 048
www.logiscenter.com



02 4792 1697
www.logiscenter.it



308 800 842
www.logiscenter.pt

About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 60,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.



All Brands Technical Service


Our Brands




Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)