



## ProLite T1531SAW

The ProLite T1531SAW-1 uses highly accurate Surface Acoustic Wave Touch Technology (SAW) with a pure-glass scratch resistive front, offering superior image clarity and screen durability. The screen can be touched with a soft stylus, finger or gloved hand making it suitable for a number of applications, and the robust design and solid but flexible stand ensures resilience in the most demanding environment. Menu Buttons are located on the side of the screen which can be locked to prevent tampering, and include a handy function to deactivate the Touch Screen for cleaning. The iiyama ProLite T1531SAW-1 Touch Screen is ideal for a wide range of applications including Point of Sale, Kiosks, Hospitality and Entertainment, Control rooms, Education, Training and many others.

### DISPLAY CHARACTERISTICS

|                     |                                                                             |
|---------------------|-----------------------------------------------------------------------------|
| Diagonal            | 15"                                                                         |
| Touchtechnology     | surface acoustic wave                                                       |
| Panel               | TN                                                                          |
| Glass hardness      | 8H minimum                                                                  |
| Display area h x w  | 228 x 304 mm; 9" x 12"                                                      |
| Response time       | 8 ms                                                                        |
| Static contrast     | 500 : 1 with touch panel                                                    |
| Brightness          | 300 cd/m² max.                                                              |
| Brightness          | 230 cd/m² with touch panel                                                  |
| Viewing zone        | horizontal/vertical: 140° / 125°; right/left: 70° / 70°; up/down: 60° / 65° |
| Display colour      | 16.7 million                                                                |
| Pixel pitch h x v   | 0.297 x 0.297 mm                                                            |
| Native resolution   | 1024 x 768 ( 0.8 megapixel)                                                 |
| Horizontal sync     | 31.5 - 60.2 KHz                                                             |
| Vertical sync       | 56 - 75 Hz                                                                  |
| Synchronization     | Separate Sync                                                               |
| Aspect ratio        | 4 : 3                                                                       |
| Light transmittance | 92%                                                                         |

### POWER MANAGEMENT

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Power supply      | AC 100 - 240 V, 50 / 60 Hz                      |
| Power Supply Unit | internal                                        |
| Power usage       | 20 W typical; max. 3 W in Power management mode |
| Power management  | VESA DPMS                                       |

### DIMENSIONS / WEIGHT

|                      |                    |
|----------------------|--------------------|
| Dimensions w x h x d | 351 x 306 x 201 mm |
| Weight               | 4.8 kg             |

### INTERFACES / CONNECTORS / CONTROLLERS

|                         |              |
|-------------------------|--------------|
| Analog input connector  | D-Sub        |
| Digital input connector | DVI-D        |
| Inputs                  | USB, RS-232C |

### SPECIAL FEATURES

|                   |                                                                                                                                                                                            |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Apple - Mac       | OS9, OSX                                                                                                                                                                                   |
| Plug & Play       | VESA DDC 2B™                                                                                                                                                                               |
| Controls          | On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Mute, Select/ Auto, Power) |
| User controls     | contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute |
| Speakers          | 2 x 1 W (Stereo)                                                                                                                                                                           |
| Anti-theft-device | Kensington-lock™ prepared                                                                                                                                                                  |
| Safety            | CE, TÜV-Bauart, Gost-R, VCCI, IP54                                                                                                                                                         |
| Tilt angle        | 90° up; 5° down                                                                                                                                                                            |
| VESA mounting     | 100 x 100 mm                                                                                                                                                                               |

### ACCESSORIES

|                      |                                                                                                                                                               |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Driver               | Windows (7, Vista, XP, 9X, 2000, CE, NT4), Linux, Mac (OSX, OS9), DOS                                                                                         |
| Included accessories | power cable, D-Sub signal cable, DVI-D signal cable, RS-232C signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), screw, quick start guide |

## ProLite T1531SR



ProLite T1531SR is based on the latest 5 Wire Resistive technology. Price / performance ratio is ideal for the budget conscious user while quality and specification is certainly not compromised. The display inputs include both Analogue and Digital (DVI) with Touchscreen connectivity via either USB or RS-232 which offers greater than typical flexibility. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree angles. Extensive Touch Utilities allow for 4 point calibration and either 9/25 point linerization. An incredibly powerful Touch solution. Available in black and white.

### DISPLAY CHARACTERISTICS

|                     |                                                                             |
|---------------------|-----------------------------------------------------------------------------|
| Diagonal            | 15"                                                                         |
| Touchtechnology     | resistive                                                                   |
| Panel               | TN                                                                          |
| Display area h x w  | 228 x 304 mm; 9" x 12"                                                      |
| Response time       | 8 ms                                                                        |
| Static contrast     | 500 : 1 with touch panel                                                    |
| Brightness          | 200 cd/m <sup>2</sup> with touch panel                                      |
| Viewing zone        | horizontal/vertical: 140° / 125°; right/left: 70° / 70°; up/down: 60° / 65° |
| Display colour      | 16.7 million                                                                |
| Pixel pitch h x v   | 0.297 x 0.297 mm                                                            |
| Native resolution   | 1024 x 768 ( 0.8 megapixel)                                                 |
| Horizontal sync     | 31.5 - 60.2 KHz                                                             |
| Vertical sync       | 56 - 75 Hz                                                                  |
| Synchronization     | Separate Sync                                                               |
| Aspect ratio        | 4 : 3                                                                       |
| Light transmittance | 80%                                                                         |

### POWER MANAGEMENT

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Power supply      | AC 100 - 240 V, 50 / 60 Hz                      |
| Power Supply Unit | internal                                        |
| Power usage       | 20 W typical; max. 2 W in Power management mode |
| Power management  | VESA DPMS                                       |

### DIMENSIONS / WEIGHT

|                      |                    |
|----------------------|--------------------|
| Dimensions w x h x d | 351 x 306 x 202 mm |
| Weight               | 4.1 kg             |

### INTERFACES / CONNECTORS / CONTROLLERS

|                         |              |
|-------------------------|--------------|
| Analog input connector  | D-Sub        |
| Digital input connector | DVI-D        |
| Inputs                  | USB, RS-232C |

### SPECIAL FEATURES

|                   |                                                                                                                                                                                            |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Apple - Mac       | OS9, OSX                                                                                                                                                                                   |
| Plug & Play       | VESA DDC 2B™                                                                                                                                                                               |
| Controls          | On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Mute, Select/ Auto, Power) |
| User controls     | contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute |
| Speakers          | 2 x 1 W (Stereo)                                                                                                                                                                           |
| Anti-theft-device | Kensington-lock™ prepared                                                                                                                                                                  |
| Safety            | CE, TÜV-Bauart, Gost-R, VCCI, IP54                                                                                                                                                         |
| Tilt angle        | 90° up; 5° down                                                                                                                                                                            |
| VESA mounting     | 100 x 100 mm                                                                                                                                                                               |
| Colour            | Black, White                                                                                                                                                                               |

### ACCESSORIES

|                      |                                                                                                                                                               |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Driver               | Windows (Vista, XP, 9X, 2000, CE, NT4), Linux, Mac (OSX, OS9), DOS                                                                                            |
| Included accessories | power cable, D-Sub signal cable, DVI-D signal cable, RS-232C signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), screw, quick start guide |



## ProLite T1532MSC

The ProLite T1532MSC 15" multi-touch screen is based on projected capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The touch function remains unaffected even if the glass is scratched. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree positioning angles. Menu Buttons are located on the side of the screen which can be locked to prevent tampering and includes a handy function to deactivate the TouchScreen for cleaning. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours. Analogue and DVI inputs are available for flexible connectivity along with USB for the Touch Interface. The multi-touch function is supported only under Windows® 7 and 8.

### DISPLAY CHARACTERISTICS

|                     |                                                                                                                        |
|---------------------|------------------------------------------------------------------------------------------------------------------------|
| Diagonal            | 15"                                                                                                                    |
| Touchtechnology     | projective capacitive, multitouch (2 compatible touch points - supported only under Windows® 7/8), activated by finger |
| Panel               | TN                                                                                                                     |
| Glass hardness      | 7H minimum                                                                                                             |
| Display area h x w  | 228 x 304 mm; 9" x 12"                                                                                                 |
| Response time       | 8 ms                                                                                                                   |
| Static contrast     | 500 : 1 with touch panel                                                                                               |
| Brightness          | 225 cd/m² with touch panel                                                                                             |
| Viewing zone        | horizontal/vertical: 140° / 125°; right/left: 70° / 70°; up/down: 65° / 60°                                            |
| Display colour      | 16.7 million                                                                                                           |
| Pixel pitch h x v   | 0.297 x 0.297 mm                                                                                                       |
| Native resolution   | 1024 x 768 ( 0.8 megapixel)                                                                                            |
| Horizontal sync     | 31,4 - 60 KHz                                                                                                          |
| Vertical sync       | 56 - 75 Hz                                                                                                             |
| Synchronization     | Separate Sync                                                                                                          |
| Aspect ratio        | 4 : 3                                                                                                                  |
| Light transmittance | 90%                                                                                                                    |

### POWER MANAGEMENT

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Power supply      | AC 100 - 240 V, 50 / 60 Hz                      |
| Power Supply Unit | internal                                        |
| Power usage       | 20 W typical; max. 2 W in Power management mode |
| Power management  | VESA DPMS                                       |

### DIMENSIONS / WEIGHT

|                      |                      |
|----------------------|----------------------|
| Dimensions w x h x d | 351 x 306.5 x 202 mm |
| Weight               | 4.5 kg               |

### INTERFACES / CONNECTORS / CONTROLLERS

|                         |                              |
|-------------------------|------------------------------|
| Analog input connector  | VGA (D-Sub)                  |
| Digital input connector | DVI-D                        |
| Inputs                  | USB (for touch connectivity) |

### SPECIAL FEATURES

|                   |                                                                                                                                                                                            |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Controls          | On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Mute, Select/ Auto, Power) |
| User controls     | contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute |
| Speakers          | 2 x 1 W (Stereo)                                                                                                                                                                           |
| Anti-theft-device | Kensington-lock™ prepared                                                                                                                                                                  |
| Safety            | CE, TÜV/Bauart, VCCI, CB, CU, IP54                                                                                                                                                         |
| Tilt angle        | 90° up; 5° down                                                                                                                                                                            |
| VESA mounting     | 100 x 100 mm                                                                                                                                                                               |
| Colour            | Black                                                                                                                                                                                      |

### ACCESSORIES

|                      |                                                                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Driver               | multi-touch: Windows7/8 (HID compliant), single-touch: Vista, XP, 9X, 2000, CE, NT4), Linux, Mac (OSX)                                                      |
| Included accessories | power cable, VGA (D-Sub) signal cable, DVI-D signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), screw, quick start guide, safety guide |



## ProLite T1532SR

ProLite T1532SR is an incredibly powerful touch solution based on the latest 5 Wire Resistive technology. Price / performance ratio is ideal for the budget conscious user while quality and specification is certainly not compromised. The display inputs include both Analogue and Digital (DVI) with Touchscreen connectivity via either USB or RS-232C which offers greater than typical flexibility. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree positioning angles. Extensive Touch Utilities allow for 4 point calibration and 9/25 point linerisation. Menu Buttons are located on the side of the screen which can be locked to prevent tampering, and includes a handy function to deactivate the Touch Screen for cleaning. In addition the bezel free design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours.

### DISPLAY CHARACTERISTICS

|                     |                                                                             |
|---------------------|-----------------------------------------------------------------------------|
| Diagonal            | 15"                                                                         |
| Touchtechnology     | resistive                                                                   |
| Panel               | TN                                                                          |
| Display area h x w  | 228 x 304 mm; 9" x 12"                                                      |
| Response time       | 8 ms                                                                        |
| Static contrast     | 500 : 1 with touch panel                                                    |
| Brightness          | 200 cd/m <sup>2</sup> with touch panel                                      |
| Viewing zone        | horizontal/vertical: 140° / 125°; right/left: 70° / 70°; up/down: 60° / 65° |
| Display colour      | 16.7 million                                                                |
| Pixel pitch h x v   | 0.297 x 0.297 mm                                                            |
| Native resolution   | 1024 x 768 ( 0.8 megapixel)                                                 |
| Horizontal sync     | 31.5 - 60.2 KHz                                                             |
| Vertical sync       | 56 - 75 Hz                                                                  |
| Synchronization     | Separate Sync                                                               |
| Aspect ratio        | 4 : 3                                                                       |
| Light transmittance | 80%                                                                         |
| Type                | bezel-free                                                                  |

### POWER MANAGEMENT

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Power supply      | AC 100 - 240 V, 50 / 60 Hz                      |
| Power Supply Unit | internal                                        |
| Power usage       | 20 W typical; max. 2 W in Power management mode |
| Power management  | VESA DPMS                                       |

### DIMENSIONS / WEIGHT

|                      |                    |
|----------------------|--------------------|
| Dimensions w x h x d | 351 x 306 x 201 mm |
| Weight               | 4.8 kg             |

### INTERFACES / CONNECTORS / CONTROLLERS

|                         |              |
|-------------------------|--------------|
| Analog input connector  | VGA (D-Sub)  |
| Digital input connector | DVI-D        |
| Inputs                  | USB, RS-232C |
|                         | D-Sub, DVI-D |

### SPECIAL FEATURES

|                   |                                                                                                                                                                                            |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Apple - Mac       | OS9, OSX                                                                                                                                                                                   |
| Plug & Play       | VESA DDC 2B™                                                                                                                                                                               |
| Controls          | On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Mute, Select/ Auto, Power) |
| User controls     | contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute |
| Speakers          | 2 x 1 W (Stereo)                                                                                                                                                                           |
| Anti-theft-device | Kensington-lock™ prepared                                                                                                                                                                  |
| Safety            | CE, TÜV-Bauart, Gost-R, VCCI, IP54                                                                                                                                                         |
| Tilt angle        | 90° up; 5° down                                                                                                                                                                            |
| VESA mounting     | 100 x 100 mm                                                                                                                                                                               |

### ACCESSORIES

|                      |                                                                                                                                                               |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Driver               | Windows (7, Vista, XP, 9X, 2000, CE, NT4), Linux, Mac (OSX, OS9), DOS                                                                                         |
| Included accessories | power cable, D-Sub signal cable, DVI-D signal cable, RS-232C signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), screw, quick start guide |



[www.logiscenter.com](http://www.logiscenter.com)  
902 050 030



[www.logiscenter.it](http://www.logiscenter.it)  
02 479 216 97



[www.logiscenter.de](http://www.logiscenter.de)  
info@logiscenter.de



[www.logiscenter.pt](http://www.logiscenter.pt)  
308 800 842

## About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permanent stock of more than 12,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.

**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.

## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables  
(labels, ribbons, PVC cards)

## Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands  
Technical Service