



CG4

UNRIVALLED PERFORMANCE,
CONVENIENCE AND VERSATILITY

FEATURES

- /// Anti-microbial Casing
- /// User Friendly Operation and Maintenance
- /// Printing Resolution of 203 / 305 dpi
- /// Real-time Clock
- /// Prints 4 inch Labels, Receipts and Tags

APPLICATIONS

- /// Healthcare
- /// General Office
- /// Government
- /// Library
- /// Retail
- /// Transportation and Logistics
- /// Entertainment

TECHNICAL INFORMATION

CG408 / CG412

PRINTING SPECIFICATION		CG408	CG412
Printing Method		Direct Thermal, Thermal Transfer	
Print Resolution, dots/mm (dpi)		8 dots/mm (203dpi)	12 dots/mm (305dpi)
Max. Print Area	Width, mm (inch)	105mm (4.13")	
	Length, mm (inch)	300mm (11.81")	
Print Speed, mm/sec (ips)		Up to 100mm/sec (4ips)	
CPU		32 bit RISC	
Printer Body Memory		Main Memory (Flash ROM): 4MB, RAM: 8 MB	

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)			
Sensor Type		I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)	
Media Type		Roll or fan-fold die cut labels, Plain paper face stock, Linerless labels, Synthetics and Continuous stock	
Media Thickness		0.06 – 0.19mm (0.002" – 0.0075")	
Label Shape	Diameter	Max. outside diameter: Ø 128mm (5.04"), Core diameter: Ø 25.4mm (1") or Ø 38mm (1.5")	
	Wind Direction	Face-in/out	
Label Size	Continuous	Width	22 – 107mm (0.87" – 4.21")
		Length	7 – 300mm (0.28" – 11.8")
	Tear-Off	Width	22 – 107mm (0.87" – 4.21")
		Length	22 – 300mm (0.87" – 11.8")
	Cutter	Width	22 – 107mm (0.87" – 4.21")
		Length	22 – 300mm (0.87" – 11.8")
	Dispenser	Width	22 – 107mm (0.87" – 4.21")
		Length	22 – 100mm (0.87" – 3.94")
Ribbon	Size	Width: 56mm (2.20") to 110mm (4.33"), Max. Length: 100m (328')	
	Core Diameter	Ø 12.7mm (0.5")	
	Wind Direction	Face-out	

FONTS / SYMBOLOGIES		
Fonts	Standard Fonts	Bitmap Fonts Alphanumeric and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)
	Rasterized Fonts	CG Times, CG Triumvirate
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°

COMMUNICATION INTERFACES	
Interface	USB + RS-232C* model, USB + LAN mode (10/100 BaseT), USB + IEEE1284 model. *RS-232C enables you to connect to PC or SATO Keypad
Command	SBPL (Ver 4.2) SATO Barcode Printer Language

OPERATING CHARACTERISTICS	
Power Requirements	
Input voltage AC100-240V (auto switching)/50W (peak) – Input voltage printer: 19V/3A	
Consumption Voltage	
At Peak: 50W, At Waiting: 2.5W	
Environment	Operating
	4 – 38°C / 30 – 80% RH (without condensing)
Storage	-10 – 60°C / 15 – 85% RH (without condensing)
Dimension	
(W x D x H): 179 x 238 x 173mm (7.05" x 9.37" x 6.81")	
Weight	
DT: 1.7kg (3.5lbs) TT: 1.9kg (4.2lbs)	

MISCELLANEOUS	
Certifications	FCC, UL, CSA, CCC, CE, ROHS compliant
Antibacterial Finishing	Resin of the enclosure / control panel includes an antibacterial substance. This substance is tested according to JISZ2801: Antimicrobial products – discourage the growth of bacteria and micro-organisms.

OPTIONS	
Accessories	Cutter, Dispenser, Real-Time Clock, Keypad, Unwinder, SATO Label Gallery™, Bluetooth (external via serial port), Smart Keyboard



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service