Product profile

PW50

Mobile Workboard Printer



- **Perfect complement for Intermec CN3, CN3e and CK61 mobile computers**
- **Convenient, integrated solution simplifies use in both portable and vehicle mount applications**
- **Optimized for DSD, Home Delivery and Field Service applications**
- **Integrated DEX communications allows easy connectivity to in-store computer system**
- **Optional magnetic stripe and smart card readers**
- **Patented power management maximizes battery life**
- **High-speed electronics and high-voltage battery deliver fast print speeds**
- **Standard communications includes Bluetooth® and serial**

Designed specifically for use with Intermec CN3, CN3e, and CK61 mobile computers, the PW50 four-inch mobile workboard printer provides a convenient, integrated solution for DSD and field service applications. With its integrated DEX communications, fast print speed, Bluetooth connectivity, and optional integrated smart card and magnetic stripe readers, the PW50 provides everything the mobile worker needs to process transactions quickly and easily.

This integrated solution provides a single convenient bundle that can easily be transported or installed in a vehicle. Custom holders safely secure the handheld computer in the mobile printer, yet allow easy removal for scanning or data entry. Hand straps and shoulder straps are available to simplify moving the equipment between the truck and the point of delivery. Drivers can easily keep batteries charged on both the printer and handheld computer: a single electrical connection through the vehicle mount or 12 volt adapter will charge both devices simultaneously.

The PW50 interfaces seamlessly with Bluetooth-enabled Intermec mobile computers including the CN3, CN3e, and CK61. Bluetooth connectivity allows the print job to be initiated whenever the handheld and printer are within wireless range of each other.

A unique design combines a high-voltage battery, patented techniques for power management, and high speed “desktop” electronics. This enables the PW50 to print the full-width of all pixels simultaneously and achieve best-in-class print speeds.

Patented power management of the robust 4-cell Li-Ion battery enables the PW50 to maintain consistent voltage to the print head for high quality printing, independent of the charge remaining in the battery. Battery capacity is designed to print 2 full rolls of receipts with 10% density text without the need to charge or change the batteries.

With 64MB of on-board Flash memory and the ability to store a full Unicode font, the PW50 gives users the flexibility to easily use multiple languages. In addition, users can improve throughput by storing frequently-used formats and graphics on the printer, eliminating the need to download large files from the mobile computer.

The PW50 combines rubberized bumpers, extra-durable gears, and a fully-integrated radio and antenna, enabling the printer to withstand the bumps and drops common to fast-paced mobile usage.

The PW50 is designed for ease of use. Paper loading, charging, and printing are fast and simple, enabling users to perform their job efficiently.

Intermec®

Physical Characteristics
Height: 180 mm (7.0 in)
Width: 310 mm (12.2 in)
Depth: 80 mm (3.2 in)
Weight: 1688 g (59.5 oz) with battery

Environmental
Operating temperature: -20°C to 50°C (-4°F to 122°F)
Storage temperature: -30°C to 70°C (-22°F to 158°F)
Charging temperature: 0°C to 40°C (32°F to 104°F)
Humidity: 10 to 90% (non-condensing)
Electrostatic Discharge:
Contact Discharge: +/-8kV
Air Discharge: +/-15kV
Sealing: IP20
Drop spec: Survives 1.2 m (4 ft) drops to concrete

Power
Battery: Rechargeable 14.8V Li-Ion, 2200mAh (4 cells); 32.56 watt hours; Battery must be ordered separately.
Recharging: 6 hours maximum
AC Adapter: 50 watts
Voltage Range: 12V +/- 5%

Memory
RAM: 16MB
Flash: 64MB

Standard Communications
RS-232 Serial (115k)
Bluetooth® (Class 1)
DEX / UCS

Optional Features
Magnetic Stripe Reader and Smart Card Reader (EMV level 1 certified)

Print Speed and Resolution
4 IPS (100 mm/s)
203 DPI (8 dots/mm)
Maximum Print Width 108 mm (4.25 in)

Media
Supports receipt media in both top coated and uncoated paper in continuous roll stock only.
Type: Direct thermal fanfold and receipt.
Media width: 111.5 mm (4.4 in)
Media length for fanfold: 25.4 mm (1.0 in) min; 609.6 mm (24 in) max
Media length for receipt: Continuous
Media thickness for receipts: 2 mil (0.05 mm) to 4.4 mil (0.112 mm)
Core ID: 19 mm (0.75 in) standard, 10mm (0.40 in) optional
Capacity: 67.3 mm (2.65 in) max. roll diameter (approximately 200", depending on media thickness)

Note: Print Speed and Environmental performance are specified for typical receipt printing applications with 10% density text.

Software Programming Language
ESC-P command sets (Line Print and EZ Print)

Character Sets
West European Latin No.1 and 9: Danish, Dutch, English Faeroese, Finnish, French, German, Icelandic, Irish, Italian, Norwegian, Portuguese, Spanish, Swedish
East European Latin No.2: Albanian, Czech, English, German, Hungarian, Polish, Rumanian, Serbo-Croatian, Slovak, Slovene
Cyrillic: Bulgarian, Byelorussian, English, Macedonian, Russian, Serbo-Croatian, Ukrainian
Arabic
Greek
Hebrew
U.S. Standard
Europe multilingual
Code Page requirements for Asian characters

Font types
40 column, normal, bold, 80 column, normal, bold, 132 column, normal, bold

Graphics
Supports user-defined fonts, graphics, formats and layouts, including custom logos

Barcode Symbologies
1D: Codabar, Code 39, Code 128, Code 128 Subset A-C, EAN-8, EAN-13, EAN-128 Subset C, Interleaved 2 of 5, UPC-A
2D: PDF 417

User Interface
LEDs and two external buttons: Standby (Power), Paper Feed
Four audio status indicators: Error alert, hardware change alert, button press alert and startup alert

Accessories
Hand strap, shoulder strap, vehicle mount, cleaning card, battery, four-bay battery charger, A/C adapter, A/C power cord, truck power cable adapter, truck power cable, forklift power cable, serial cable.

Approvals
North America UL and cUL Listed, UL 60950-1
Europe - GS Licensed, EN 60950-1
Mexico NYCE Certified, NOM 19
Other Countries IEC 60950-1
EMC Approvals
USA FCC Title 47, Part 15, Subpart B, Class B;
Europe EMC Directive (EN55022 Class B + EN55024) ; CISPR22

Warranty
One year; additional Medallion service packages available

North America Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

South America & Mexico Headquarters Office
Newport Beach, California
Phone: (949) 955-0785
Fax: (949) 756-8782

Europe/Middle East & Africa Headquarters Office
Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific Headquarters Office
Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet
www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales
Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW: 00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales
Phone: (425) 348-2762

Media Sales
Phone: (513) 874-5882

Customer Service and Support
Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.

611880- 01A 04/08

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Solutions for Automatic Identification, Barcodes and Mobility

More than 3000 customers in 15 countries • More than 12,000 products in stock

www.logiscenter.com
902 050 030

www.logiscenter.it
02 479 216 97

www.logiscenter.de
info@logiscenter.de

www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the befenits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permament stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Our Brands

MOTOROLA
ZEBRA TECHNOLOGIES
Intermec
Honeywell
DATALOGIC
datamax·o'neil
Metrologic
LXE
EPSON
elo
star
unitech
PRINTRONIX
symbol

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers




Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

All Brands Technical Service

GRUPO LOGISCENTER, S.L. - The Barcode Solutions Center
Av. Puente Cultural 10-A • 28702 San Sebastián de los Reyes - MADRID (Spain)
CIF ES B85538601 • info@logiscenter.com • www.logiscenter.com