



MS842

2D Imager Scanner

The Unitech MS842 combines efficiency, durability and reliability into a compact, lightweight handheld scanner. Supporting all common 1D and 2D barcodes, the MS842 can be used in a wide variety of markets and applications.

Efficiency at the highest level

With the seamless integration of its high-performance decoder and scan engine, the MS842 provides one of the most efficient scanning solutions in its class. It excels in demanding applications like event ticket scanning and security, industrial shipment management and inventory control in pharmacies. Featuring an extended depth of field, wide scan angle and aggressive scan rate, the MS842 provides performance and reliability wherever it is used.

Durability & low cost of ownership

Accidents happen in every business setting, and the MS842 is ruggedly designed to perform under adverse conditions. With its durable construction, the MS842 can withstand a 6-foot fall to concrete. So, if a worker happens to drop their scanner, they can pick it up and continue scanning without interruption. No downtime, no replacement, and no service needed. The MS842 also features an IP42-rated environmental seal against moisture and dust, and an extended-life trigger design that guarantees 10 million scans before failure.

Practical and compact

Certain industries, such as retail and transportation, consist of very scan-intensive work environments. At a mere 7 ounces, the MS842 is very user friendly and ideal for those tasks that require high volume scanning. The ergonomic and compact design reduces fatigue and ensures user comfort during periods of extensive scanning. And with two operational modes, trigger mode and presentation mode, the MS842 simply allows users the freedom to do more.

Main Features:

- High performance engine & decoder
- Supports all 1D and 2D barcodes
- Long-life trigger design
- Scans mobile phones and computer displays
- Durable construction: IP42 seal / 6-foot drop threshold
- Lightweight: 5.9 oz without USB cable / 7 oz with USB cable

Optical & Performance

Receiving Device	Image Sensor, 752 x 480 pixels
Light Source	Illumination : 625 nm LED Aiming : 655 nm VLD
Max. Resolution	SR: 5 mil (code 39), 6.7 mil (PDF417) HD: 3 mil (code 39), 4 mil (PDF417)
Skew Angle	±60 degrees
Scan Angle	±60 degrees
Reading Distance	(DOF PCS=80%)

SR	near	far
Code 39, 5mil	5.3cm	19.1cm
PDF417, 6.7mil	8.6cm	18.0cm

SR	near	far
Code 39, 3mil	4.1cm	9.7cm
PDF417, 4mil	4.6cm	18.0cm

*=dependent on width of bar code

Functionality

Symbologies	1D: Code 39, Full ASCII Code39, Interleave 2 of 5, Standard 2 of 5, UPC A/E, Delta Code, Label Code, MSI/ Plessy, Codabar, Code 11, EAN8/13, Code 93, Code 128, EAN128, Code32, Toshiba Code, GS1 databar Code. 2D: PDF417, MicroPDF417, Datamatrix, QR Code, Micro QR Code, Aztec, RSS, Composite, TLC -39, MaxiCode. Postal: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX)
Operation Mode	Trigger mode, Auto scan mode
Data Formatting	Prefix, Suffix, Code ID, Reformatting Date

Electrical

Operation Voltage	5VDC ±0.25V
Current Consumption	Operation mode: <400mA Standby mode: <160mA

Mechanical

Scanner Dimension	6.93"H x 2.91"W x 3.50"D
Scanner Weight	7 ounces (without cable)
Switch life	10 million time

Environmental

ESD Protection	Functional after 8K Contact and 12K Air
Mechanical Shock	1.8m onto concrete (scanner only)
Operating temperature	0°C to 50°
Storage temperature	-30°C to 70°C
Relative Humidity	95% non-condensing
IP rate	IP42

Communication

USB, RS232

Accessories

Hand-free stand
Interface cable

Regulatory Approvals

CE, FCC, BSMI, VCCI



Specifications subject to change without notice.

Copyright 2011 Unitech Electronics Co., Ltd.
All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd.

All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

us.ute.com

Unitech America, Inc. | 6182 Katella Avenue | Cypress, CA 90630
714-891-6400 ph | 800-861-8648 toll | 714-891-5050 fx



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service