


TPTCM112III

112mm ticket / receipt printer

- Best printing quality (200 DPI)
- Paper width: 112mm
- Paper thickness: from 63 to 100 µm
- Printing > 140 mm/sec
- Up to 160mm paper roll diameter
- RS232 + USB interfaces
- Highly reliable cutter: > 1,000,000 cuts
- Sensors: ticket presence, near paper end, black mark and label gap (optional)



CHARACTERISTICS

- 1D/ 2D (QRCODE) barcode printing feature
- International fonts on-board: any language available
- Label gap and black mark sensors (optional)
- Strong motorised dispenser available
- Versatile: **optional** paper roll holder - 5 positions
- Illuminated paper outfeed (LED)
- Plastic paper bezel (optional)
- Sturdy and reliable: robust and light mechanical parts
- DIN power supply connector
- Cut&drop version available
- Plastic paper bezel (optional)

APPLICATIONS

- Self-service kiosks
- Information kiosks
- Form and document kiosks
- Banking machines and cash dispensers

ACCESSORIES

What is in the box:


- Model 915KV010100300: Device
- Models 915KV010200300 and 915KV010400300: Device, paper guide bracket with 2 fixing screws
- Model 915KV010300300: Device, paper guide brackets (internal and external) with 4 fixing screws

---


TECHNICAL SHEET

Printing Method	Thermal with fixed head
Number of dots	8 dots/mm
Resolution	203 DPI
Printing (mm/sec)	>140 mm/sec
Character set	International (default), Chinese, Korean
Supported Barcode	UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, AZTEC, QRCODE
Printing Format	Height and width from 1 to 8, bold, negative, underlined, script
Printing Direction	Straight, 90°, 180°, 270°
Paper width	112 mm
Paper weight	from 60 to 90 g/m^2
Paper thickness	from 63 to 100 µm
Roll Dimension	Max 160mm (120mm without roll holder)
Emulation	CUSTOM/POS, TPTCMII
Interfaces	RS232 + USB
Data Buffer	16 KB
Flash Memory	1MB internal, 4MB external
RAM Memory	128Kb internal, 8MB external
Drivers	Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); Android™
Software Tools	PrinterSet, CustomPowerTool, Status Monitor
Power supply	24 Vdc±10%
Medium consumption	1.7A (12.5% dots turned on)
MTBF	122,000 hours (electronic board)
Head Life	100 Km / 100M pulses
MCBF	1,000,000 cuts
Operating temperature	0°C + 50°C
Dimensions	227.4(L)x95.3(H)x171.5(W) mm with short paper mouth 300(L)x95.3(H)x171.5(W) mm with dispenser
Weight	1.7 Kg (without ejector)2.1 Kg (with ejector)


MODELS




915KV010200300
PRINTER TPTCM112III CUTTER AND NOTCH



915KV010400300
PRINTER TPTCM112III LABEL AND CUTTER



915KV010300300
PRINTER TPTCM112III STRONG CUTTER



915KV010100300
PRINTER TPTCM112III USB RS232 EJECTOR

CUSTOM S.P.A. - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.
Last update: 09 March 2022