



1517L 15" LCD Desktop Touchmonitor

The Elo Touch Solutions 1517L is a flexible, space-saving, standard aspect ratio 15-inch LCD touchmonitor well-suited to meet the durability and aesthetic requirements for front-of-store, back office, kiosk and even out-of-store applications.

The Elo 1517L offers true versatility for a variety of retail and hospitality interactive solutions including:

- Point-of-sale (POS)
- Point-of-service
- Loyalty systems
- Countertop kiosk point-of-information
- Back office solutions integrating labor management and inventory analysis
- Shelf-level/countertop interactive digital signage displays

Available with a choice of two no-bezel touchscreen technologies, iTouch surface acoustic wave or AccuTouch resistive, the 1517L provides stable, "drift-free" operation with excellent image clarity, resolution, and light transmission—for an accurate touch response and vivid images! The 1517L is distinctive by incorporating state-of-the-art LED backlights that reduce the energy consumption of the higher energy consumption of CCFL backlights often used by other touchmonitors.

Features and Benefits

- Choice of two Elo leading zero-bezel touchscreen technologies:
 - iTouch surface acoustic wave
 - AccuTouch resistive
- Zero-bezel touchscreen for seamless, easy to-clean glass-to-edge design
- 4:3 aspect ratio panel
- USB touch controller, VGA port
- LED backlighting allows for state-of-the-art slim design, while reducing power consumption
- Removable base and mounting features, including a VESA mount as well as wall- and arm-mounting options for installation flexibility
- Ruggedized for use in high-traffic environments
- Optional peripherals include field-installable 3-stripe MSR and various display stands
- Up to 1024 x 768 resolution at 75Hz
- Mounting holes on base bottom for tabletop security
- Controls on the side, plus lockout function for public use
- Digital on-screen display (OSD)
- Worldwide agency approvals

1517L 15" LCD Desktop Touchmonitor

Computer Specifications

Model	1517L
Color	Black or white
Active Display Area	11.97" x 8.98" (304.13mm x 228.096mm)
Dimensions* (without stand and packaging)	14.09" x 12.88" x 1.73" (358.1mm x 285mm x 44.1mm) max
LCD Technology	Active matrix TFT LCD
Diagonal Size	15"
On-Screen Display (OSD)	Accessible through switches along the bottom. Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Volume, Mute, Recall Defaults, Video Source; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power
Mounting Options*	VESA 4-hole 75mm mounting interface on rear of unit; 3-hole threaded mounting on bottom of stand
Aspect Ratio	4:3
Native Resolution	1024 x 768
Preset Video Timings	640 x 480 60Hz,75Hz; 720 x 400 70Hz; 800 x 600 56, 60Hz,75Hz; 1024 x 768 60Hz,75Hz
Number of Colors	16.7 million
Brightness (typical)	LCD Panel: 250 nits; with iTouch: 225 nits; with AccuTouch: 200 nits
Response Time (Tr + Tf) (typical)	8-25 msec
Viewing Angle (typical)	Horizontal: 160°; Vertical: 140°
Contrast Ratio (typical)	700:1
Video	Analog VGA on Female DE-15 connector; Input Video Horizontal Sync frequency range: 31.5-80KHz Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	Monitor input power connector: Coaxial power jack (2.1mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC $\pm$ 5%. Note: This monitor is sold with an AC-DC power adapter. Adapter input connector: IEC 60320 C14; Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (Typical): ON (monitor + AC/DC adapter): 10W; SLEEP (monitor + AC/DC adapter): 1.1W; OFF (monitor + AC/DC adapter): 1.0W
Weight (with stand)	Unpackaged: 9.0 lbs (4.1kg); Packaged: 14.9 lbs (6.8kg)
Weight (without stand and packaging)	6.0 lbs (2.73kg)
Shipping Dimensions	17.16" x 14.56" x 7.67" (436mm x 370mm x 195mm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 60°C)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	C-Tick; cUL, IC; CCC; CE; VCCI; KCC, e-Standby; BSMI Mark; UL, FCC; CB; RoHS, China RoHS, WEEE, IMERC
Warranty	3 years
MTBF	50,000 hours demonstrated

*See dimensional drawings for details

For updated specifications and more information, please visit www.elotouch.com.

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
301 Constitution Drive
Menlo Park, CA 94025-1110
800-ELO-TOUCH
Tel 1-650-361-4800
Fax 1-650-361-4722
customerservice@elotouch.com

Europe

Tel +32 (0)16 35 21 00
Fax +32 (0)16 35 21 01
elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161
Fax +81 (45) 478-2180
www.tps.co.jp

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com.ar

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. AccuTouch, Elo (logo), Elo Touch Solutions and iTouch are trademarks of Elo Touch Solutions, Inc.

Copyright 2012 Elo Touch Solutions, Inc. All rights reserved. 07/12



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Our Brands



MOTOROLA



Intermec

Honeywell

DATALOGIC



datamax • o'neil

Metrologic

LXE

EPSON

elo

star

unitech

PRINTRONIX

symbol



**All Brands
Technical Service**


Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers




Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)