GLANCETRON

# GT-15 WIDE

**Professional wide format touch screen**



- High-end 39.6 cm (15.6“) LCD widescreen monitor
- Integrated touch screen with 5-wire resistive touch technology
- Elegant design and particularly robust construction
- Dual touch screen interface: RS232/USB
- Maximum resolution: 1366 x 768 pixels

## Specifications

| | | |
|---|---|---|
| Display | Screen diagonal / type | 39.6 cm (15.6“) / LCD TFT active matrix |
| | Aspect ratio | 16:9 |
| | Resolution (max.) | 1366 x 768 Pixel |
| | Active area (WxH) | 344,2 x 193,5 mm |
| | Response time | Tr: 2 ms / Tf: 6 ms |
| | Colours | 16.7 million |
| | Contrast | 500:1 |
| | Brightness | 200 cd/m² |
| | Viewing angle (H/V) | 90° / 65° |
| | Video input | VGA (analogue) |
| | Touch technology | Resistive (5-wire) |
| | Touchinterface | Dual interface (RS232/USB) |
| General | Colour | Dark grey |
| | Dimensions (WxHxD) | 388.3 x 272.2 x 214.2 mm (incl. stand)<br>388.3 x 237.5 x 58.1 mm (without stand) |
| | Weight | 4,8 kg |
| | Power supply | External power supply (DC 12 V / 4.15 A) |
| | Power consumption | Operating: 20 W / Sleep: 4 W / Standby: 2 W |
| | Mounting options | Stand / VESA (75 x 75mm) |
| | Control buttons | Power on/off, Menu, Select, Up, Down |
| | Audio | 1 W speaker / 2-channel |
| | Certifications | TUV, CE, UL, CUL, FCC, RoHS, IPX1 |
| | Drivers | Windows 7, Vista, XP, 2000, ME, 98, NT4.0, CE, XP Embedded;<br>Linux; Apple MacOS |
| | Options | n/a |
| | Delivery contents | Monitor, stand, connection cables (USB,RS232, VGA, audio), power supply, power cord (EU), cable cover, driver CD, QSG |
| Environment | Operating temperature | 0 to +40 °C |
| | Storage temperature | -20 to +60 °C |
| | Operating humidity | 20 to 80 % (non-condensing) |
| | Storage humidity | 10 to 90 % (non-condensing) |








Your partner

Errors excepted; subject to change.
Rev. 2.0

GLANCETRON

# GT-19 WIDE

**Professional wide touch screen**



- High-end 47 cm (18.5“) LCD monitor for demanding applications
- Integrated touch screen with 5-wire resistive touch technology
- Elegant design and particularly robust construction
- Dual touch screen interface: RS232/USB
- Maximum resolution: 1366 x 768 pixels

## Specifications

| | | |
|---|---|---|
| Display | Screen diagonal / type | 47 cm (18.5“) / LCD TFT active matrix |
| | Aspect ratio | 16:9 |
| | Resolution (max.) | 1366 x 768 Pixel |
| | Active area (WxH) | 409,8 x 230,4 mm |
| | Response time | Tr: 3,6 ms / Tf: 1,4 ms |
| | Colours | 16.7 million |
| | Contrast | 1000:1 |
| | Brightness | 200 cd/m² |
| | Viewing angle (H/V) | 170° / 160° |
| | Video input | VGA (analogue) |
| | Touch technology | Resistive (5-wire) |
| | Touch interface | Dual interface (RS232/USB) |
| General | Colour | Dark grey |
| | Dimensions (WxHxD) | 457.8 x 312.2 x 214.2 mm (incl. stand)<br>457.8 x 278.4 x 60 mm (without stand) |
| | Weight | 5,7 kg |
| | Power supply | External power supply (DC 12 V / 4.15 A) |
| | Power consumption | Operating: 25 W / Sleep: 4 W / Standby: 2 W |
| | Mounting options | Stand / VESA (100 x 100 mm) |
| | Control buttons | Power on/off, Menu, Select, Up, Down |
| | Audio | 1W speaker / 2-channel |
| | Certifications | TUV, CE, UL, CUL, FCC, RoHS, IPX1 |
| | Drivers | Windows 7, VISTA, XP, 2000, ME, 98, NT4.0, CE, XP Embedded;<br>Linux; Apple MacOS |
| | Options | n/a |
| | Delivery contents | Monitor, stand, connection cables (USB, RS232, VGA, audio),<br>power cord (EU), cable cover, driver CD, QSG |
| Environment | Operating temperature | 0 to +40 °C |
| | Storage temperature | -20 to +60 °C |
| | Operating humidity | 20 to 80 % (non-condensing) |
| | Storage humidity | 10 to 90 % (non-condensing) |








Your partner

Errors excepted; subject to change.
Rev. 2.0

# Solutions for Automatic Identification, Barcodes and Mobility

*More than 3000 customers in 15 countries • More than 12,000 products in stock*


www.logiscenter.com
902 050 030

www.logiscenter.it
02 479 216 97

www.logiscenter.de
info@logiscenter.de

www.logiscenter.pt
308 800 842


## About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the befenits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permament stock of more than 12,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.

**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.

## Our Brands

MOTOROLA
ZEBRA TECHNOLOGIES
Intermec
Honeywell
DATALOGIC
datamax·o'neil
Metrologic
LXE
EPSON
elo
star
unitech
PRINTRONIX
symbol

## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers




Barcode readers



Data terminals & PDA



PVC card printers




RFID



Consumables
(labels, ribbons, PVC cards)

**All Brands Technical Service**


GRUPO LOGISCENTER, S.L. - The Barcode Solutions Center
Av. Puente Cultural 10-A • 28702 San Sebastián de los Reyes - MADRID (Spain)
CIF ES B85538601 • info@logiscenter.com • www.logiscenter.com