DCS & Labelling Worldwide



M10e

WIDE WEB

FEATURES

- Chemical – Drum Labels
- Fast Print Speed of up to 125 mm/sec
- Automatic Label Loading via Label Edge Sensor
- High Quality Printing up to 305 dpi
- Extra-wide (267 mm) Printing Area for Giant Labels or Multiple Labels per page

APPLICATIONS

- Electronics
- Automotive
- Industrial
- Steel Mill
- Forestry
- Chemical

TECHNICAL INFORMATION

M10e

PRINTING SPECIFICATION			M10e
Printing Method			Direct Thermal and Thermal Transfer
Print Resolution, dots/mm (dpi)			12 dots/mm (305dpi)
Max. Print Area	Width, mm (inch)		267mm (10.5")
	Length, mm (inch)		420mm (16.5")
Print Speed, mm/sec (ips)			Up to 125mm/sec (5ips)
CPU			32 bit RISC

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)			
Sensor Type			I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)
Media Type			Roll or fan-fold die cut labels, Plain paper face stock, Synthetics and Continuous stock
Media Thickness			0.08 – 0.21mm (0.003" – 0.008")
Label Shape*	Diameter		Max. outside diameter: Ø 203mm (8"), Core diameter: Ø 76.2mm (3")
	Wind Direction		Face-in
Label Size	Continuous	Width	128 – 297mm (5.04" – 11.7")
		Length	40 – 420mm (1.57" – 16.5")
	Tear-Off	Width	128 – 297mm (5.04" – 11.7")
		Length	40 – 420mm (1.57" – 16.5")
	Cutter	Width	128 – 297mm (5.04" – 11.7")
		Length	40 – 420mm (1.57" – 16.5")
Ribbon	Size		Width: 145mm (5.71") to 273mm (10.7"), Max. Length: 300m (984')
	Core Diameter		Ø 25.4mm (1")
	Wind Direction		Face-in

FONTS / SYMBOLOGIES		
Fonts	Standard Fonts	Bitmap Fonts Alphanumerical and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)
	Rasterized Fonts	CG Times, CG Triumvirate
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW–7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°

COMMUNICATION INTERFACE	
Optional Plug-in Interface	IEEE1284, Centronics parallel, RS232C (2400-19,200 Baud), RS232C highspeed (9,600-57,600 baud), USB (12Mbit/s), LAN (TCP/IP protocol 10/100BaseT), Wireless LAN 802.11b/g

OPERATING CHARACTERISTICS		
Power Requirements		Input voltage AC100-240V (auto switching)/560W (peak)
Environment	Operating	5 – 40ºC / 30 – 80% RH (without condensation)
	Storage	-5 – 60ºC / 30 – 90% RH (without condensation)
Dimension		(W x D x H): DT: 475 x 313.4 x 274.2mm (18.7" x 12.3" x 10.8"), TT: 475 x 313.4 x 319.2mm (18.7" x 12.3" x 10.8")
Weight		DT: approx. 20.2g (0.04 lbs), TT: approx. 21.2g (0.05 lbs)

MISCELLANEOUS		
Certifications		FCC, UL, CSA, CCC, CE, ROHS compliant
Function	Useful Features	Hex dump, Print custom character design, Graphic, Sequential numbering for number and barcode, Form storage and recall for faster data retrieving of complex formats
	Self Diagnosis Checking	Head check, Paper end detection, Ribbon end / Near-end detection (remaining 15m – 30m detection), Open cutter-cover detection, Auto sensing for continuous forms, Memory card error detection, Test print
	Operational Panel	16 x 2 Line alphanumeric, Three LED to indicate error, power and status
	DIP Adjustment	Print position adjustment, Cutting / tear-off position adjustment, Print darkness adjustment, LCD contrast adjustment

OPTIONS	
Accessories	Cutter, Unwinder, Stacker, Expansion Memory, PCMCIA Add-on Memory, Smart Keyboard, SATO Label Gallery™

*When using the UWM10e unwinder. The standard M10e only allows fanfold labels.

SATO makes no guarantee that the above features are available in all models, and specifications are liable to change, without notice. Version 09/10. * Measurements are approximate values.

Solutions for Automatic Identification, Barcodes and Mobility

More than 3000 customers in 15 countries • More than 12,000 products in stock

www.logiscenter.com
902 050 030

www.logiscenter.it
02 479 216 97

www.logiscenter.de
info@logiscenter.de

www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the befenits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permament stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Our Brands

MOTOROLA
ZEBRA TECHNOLOGIES
Intermec
Honeywell
DATALOGIC
datamax·o'neil
Metrologic
LXE
EPSON
elo
star
unitech
PRINTRONIX
symbol

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers




Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

All Brands Technical Service

GRUPO LOGISCENTER, S.L. - The Barcode Solutions Center
Av. Puente Cultural 10-A • 28702 San Sebastián de los Reyes - MADRID (Spain)
CIF ES B85538601 • info@logiscenter.com • www.logiscenter.com