



**TTP-244 PRO** – Desktop Thermal Transfer Bar Code Printer  
**AFFORDABLE PRICE, FAST PERFORMANCE,  
WON'T BREAK YOUR BAR CODE BUDGET**



#### KEY FEATURES

- 200 MHz 32-bit RISC processor with 8 MB SDRAM, 4MB Flash memory
- Internally scalable true type fonts
- TSPL-EZ™ firmware emulates Eltron® and Zebra® languages out of the box
- Dual-motor gear driven design
- 300 meter (984') ribbon supply on a 25.4 mm (1") core (coated side out)
- 110 mm (4.3") OD internal media supply, optional external roll mount supports 214 mm (8.4") OD label rolls on 76.2 mm (3") core
- 5 inches per second print speed
- USB 2.0 & RS-232 interfaces standard
- Free bundled labeling software and Windows drivers
- Features an industry best 2 years limited warranty

#### APPLICATIONS

- Shipping & Receiving
- Compliance Labeling
- Asset Tracking
- Inventory Control
- Document Management
- Shelf Labeling & Product Marking
- Specimen Labeling & Patient Tracking

## TTP-244 PRO – Desktop Thermal Transfer Bar Code Printer

| PRINTER MODEL                 | TTP-244 PRO                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Resolution                    | 8 dots/mm (203 DPI)                                                                                                                                                                                                                                                                                                                                                                                   |
| Printing method               | Thermal Transfer & Direct Thermal                                                                                                                                                                                                                                                                                                                                                                     |
| Max. print speed              | 127 mm (5")/second                                                                                                                                                                                                                                                                                                                                                                                    |
| Max. print width              | 108 mm (4.25")                                                                                                                                                                                                                                                                                                                                                                                        |
| Max. print length             | 2,286 mm (90")                                                                                                                                                                                                                                                                                                                                                                                        |
| Enclosure                     | ABS plastic                                                                                                                                                                                                                                                                                                                                                                                           |
| Physical dimension            | 232 mm (W) x 156 mm (H) x 288 mm (D)<br>9.13" (W) x 6.14" (H) x 11.34" (D)                                                                                                                                                                                                                                                                                                                            |
| Weight                        | 2.5 kg (5.51 lbs)                                                                                                                                                                                                                                                                                                                                                                                     |
| Label roll capacity           | 110 mm (4.33") OD                                                                                                                                                                                                                                                                                                                                                                                     |
| Ribbon                        | 300 m long, max. OD 67 mm, 1" core (ink coated outside)                                                                                                                                                                                                                                                                                                                                               |
| Ribbon width                  | 40 mm ~ 110 mm (1.6" ~ 4.3")                                                                                                                                                                                                                                                                                                                                                                          |
| Processor                     | 32-bit RISC CPU                                                                                                                                                                                                                                                                                                                                                                                       |
| Memory                        | <ul style="list-style-type: none"> <li>• 4 MB Flash memory</li> <li>• 8 MB SDRAM</li> <li>• SD card reader for Flash memory expansion, up to 4 GB (user option)</li> </ul>                                                                                                                                                                                                                            |
| Interface                     | <ul style="list-style-type: none"> <li>• USB 2.0</li> <li>• RS-232</li> <li>• Centronics (factory option)</li> <li>• Bluetooth (user option)</li> <li>• External 802.11 b/g/n wireless (user option)</li> </ul>                                                                                                                                                                                       |
| Power                         | External universal switching power supply<br>• Input: AC 100-240V, 2.5A, 50-60Hz<br>• Output: DC 24V, 2.5A, 60W                                                                                                                                                                                                                                                                                       |
| Operation switch, button, LED | 1 power switch, 1 feed button & 3 LED (Power, Error, On-line)                                                                                                                                                                                                                                                                                                                                         |
| Sensors                       | <ul style="list-style-type: none"> <li>• Gap transmissive sensor</li> <li>• Black mark reflective sensor</li> <li>• Ribbon end sensor</li> </ul>                                                                                                                                                                                                                                                      |
| Internal fonts                | <ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> </ul>                                                                                                                                                                                                                |
| Bar code                      | <ul style="list-style-type: none"> <li>• 1D bar code<br/>Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11</li> <li>• 2D bar code<br/>PDF-417, Maxicode, DataMatrix, QR Code, Aztec</li> </ul>                                      |
| Font and barcode rotation     | 0, 90, 180, 270 degree                                                                                                                                                                                                                                                                                                                                                                                |
| Printer language              | TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II)                                                                                                                                                                                                                                                                                                                                                             |
| Media type                    | Continuous, die-cut, black mark, fan-fold, notched (outside wound)                                                                                                                                                                                                                                                                                                                                    |
| Media width                   | 25.4 ~ 112 mm (1.0" ~ 4.4")                                                                                                                                                                                                                                                                                                                                                                           |
| Media thickness               | 0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)                                                                                                                                                                                                                                                                                                                                                                      |
| Media core diameter           | 25.4 ~ 76.2 mm (1" ~ 3")                                                                                                                                                                                                                                                                                                                                                                              |
| Label length                  | 10 ~ 2,286 mm (0.39" ~ 90")                                                                                                                                                                                                                                                                                                                                                                           |
| Environment condition         | Operation: 5 ~ 40°C, 25 ~ 85% non-condensing<br>Storage: -40 ~ 60°C, 10~ 90% non-condensing                                                                                                                                                                                                                                                                                                           |
| Safety regulation             | FCC Class A, CE Class A, C-Tick Class A, TÜV/Safety, CCC                                                                                                                                                                                                                                                                                                                                              |
| Environmental concern         | Comply with RoHS, WEEE                                                                                                                                                                                                                                                                                                                                                                                |
| Accessories                   | <ul style="list-style-type: none"> <li>• Windows labeling software CD disk</li> <li>• Quick start guide</li> <li>• Power cord</li> <li>• External universal switching power supply</li> <li>• Label spindle, fixing tab x 2</li> <li>• Ribbon spindle x 2</li> <li>• Ribbon paper core</li> </ul>                                                                                                     |
| Limited warranty              | <ul style="list-style-type: none"> <li>• Printer: 2 years</li> <li>• Print head: 25 km (1 million inches) or 12 months which comes first</li> <li>• Platen: 50 km (2 million inches) or 12 months which comes first</li> </ul>                                                                                                                                                                        |
| Factory options               | • Centronics parallel & RS-232 serial interfaces                                                                                                                                                                                                                                                                                                                                                      |
| Dealer options                | N/A                                                                                                                                                                                                                                                                                                                                                                                                   |
| User options                  | <ul style="list-style-type: none"> <li>• Bluetooth module (serial interface)</li> <li>• 802.11 b/g/n wireless module (serial interface)</li> <li>• External roll mount, media OD. 214 mm (8.4") on a 1" or 3" core</li> <li>• SD Flash memory card reader</li> <li>• 3" core label spindle</li> <li>• KP-200 Plus keyboard display unit</li> <li>• KU-007 Plus programmable smart keyboard</li> </ul> |



### CORPORATE HEADQUARTERS

**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 2 2218 6789  
 E-mail: apac\_sales@tscprinters.com

### LI ZE PLANT

**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 3 990 6677  
 E-mail: americas\_sales@tscprinters.com

### AMERICAS

**TSC Auto ID Technology America Inc. Corporate Office**  
 Tel: +1 909 612 9606  
 E-mail: americas\_sales@tscprinters.com

### Orlando Office

Tel: +1 407 704 8918  
 E-mail: americas\_sales@tscprinters.com

### CANADA

**TSC Auto ID Technology America Inc.**  
 Tel: +1 909 612 9606  
 E-mail: americas\_sales@tscprinters.com

### MEXICO

**TSC Mexico Representative Office**  
 Tel: +52 (33) 3836 6682  
 E-mail: americas\_sales@tscprinters.com

### BRAZIL

**TSC Brazil Representative Office**  
 Tel: +55 (11) 9597 8098  
 E-mail: americas\_sales@tscprinters.com

### EMEA

**TSC Auto ID Technology EMEA GmbH**  
 Tel: +49 (0) 8106 37979 00  
 E-mail: emea\_sales@tscprinters.com

### RUSSIA

**TSC Auto ID Technology EMEA GmbH**  
 Tel: +7 915 422 8889  
 E-mail: emea\_sales@tscprinters.com

### MIDDLE EAST

**TSC Auto ID Technology ME Ltd, FZE**  
 Tel: +971 4 2533 069  
 E-mail: emea\_sales@tscprinters.com

### ASIA PACIFIC

**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 2 2218 6789  
 E-mail: apac\_sales@tscprinters.com

### CHINA

**Tianjin TSC Auto ID Technology Co., Ltd.**  
 Tel: +86 22 5981 6661  
 E-mail: apac\_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.  
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.  
 © 2014 TSC Auto ID Technology Co., Ltd.  
 Product models and Specifications are subject to change without notice.  
 Contact your TSC sales representative for specific information.



800 729 0236  
www.logiscenter.us



0241 9550 9225  
www.logiscenter.de



01 82 88 44 70  
www.logiscenter.fr



020 3318 8265  
www.logiscenter.co.uk



0720 115814  
www.logiscenter.at



02 58 80 583  
www.logiscenter.be



911 433 048  
www.logiscenter.com



02 4792 1697  
www.logiscenter.it



308 800 842  
www.logiscenter.pt

## About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permanent stock of more than 60,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.

**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.



## All Brands Technical Service


## Our Brands




## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables  
(labels, ribbons, PVC cards)