

ML910™

Rugged Notebook



KEY FEATURES

The full-sized, feature-rich ML910 Rugged Notebook features a sunlight readable, high resolution LCD Panel that provides high quality detailed graphical images on a 13.3" Touchscreen display.

Configurable Media Bay with numerous options

Supports a wide range of wireless options including embedded EVDO/1xRTT, embedded

GPRS/EDGE/UMTS, Motorola Private DataTAC, 802.11abg, GPS and Bluetooth®

Innovative antenna design

Optimized thermal management solution

Field replaceable three dimensional shock absorber mounted hard drive with heater

Magnesium alloy and plastic housing is fully sealed; meets rigorous

environmental specs of MIL-STD-810F

Intel® Core™ Duo or Core 2 Duo Processor

Fingerprint image reader provides convenience and security

Motorola's Advanced Dock Solution with hot-docking capability and automatic antenna switching

With more than 80 years of technological innovations and over 30 years of wireless data expertise, Motorola has an answer for your mobile data needs.

Top to bottom, handle to hinge, the ML910 is Motorola-designed and developed for remarkable flexibility, versatility and durability. This ultra-robust, ruggedized notebook meets and exceeds MIL-STD-810F standards. Full-sized and full-featured, it is our most advanced rugged notebook computer, ready to handle the demands of the mission-critical world.

Experience Motorola quality and design with advanced features such as an Intel dual core processor; shock mounted removable 80 or 120 GB

hard drive with heater; high-resolution, glare-free WXGA (16:9) screen; full-sized 13.3" touch display; Configurable Media Bay with optional: CD RW/DVD ROM, CD RW / DVD RW, or Secondary Battery; fingerprint ID reader for added security; fully-sealed backlit keyboard; automatic GPS external antenna switching with advanced hot-dock solution; on-board digital video recorder.

For the most complete set of wireless options in a rugged design – choose the ML910 Rugged Notebook!

SPECIFICATION SHEET

ML910™
Rugged Notebook

SYSTEM FUNCTION (ML910)

CPU	Processor: Intel® Core™ Duo 1.66GHz (L2400) or Core 2 Duo 1.5GHz (L7400) L2 Cache: 2MB with Core Duo; 4MB with Core 2 Duo FSB: 667MHz
Memory	1 GB Standard, 4 GB Maximum (Total usable memory will be less, depending on configuration)
Video Graphics Adapter	ATIMobility Radeon™ X1400 (dedicated 128MB) MotionComp capability, support hardware aid for DVD playback Supports Dual View function LCD/CRT simultaneous display capability
Display	13.3" transmissive WXGA (1280 x 800) LCD with touch screen 500+ NIT Brightness. Touchscreen can be used with gloves.
Hard Disk Drive	80 GB standard shock-mounted, with heater; Optional: 120 GB hard disk drive
Drive Bay	Configurable Media Bay, Options: CD RW / DVD ROM (Combo Drive), CD RW/ DVD RW (Dual Drive), Secondary Battery
Floppy Disk Drive	External USB floppy (optional)
Keyboard	Full travel QWERTY, fully-sealed backlight keyboard; rubberized backlight keyboard (optional)
Pointing Device	Touchpad with 4 programmable buttons
Fingerprint Scanner	500dpi (requires customer provided software application)
PCMCIA	1x External Type II - Cardbus support (Accessory PCMCIA to pci Express 34 converter card included)
Audio	AC97 Audio Support, MS-Sound Compatible High Definition Audio Codec (Azalia Compliant) Built-in speakers (stereo) Microphone In Port Earphone/Speaker Out Port/ S/PDIF Output Port
I/O Port	1x Serial 3x USB 2.0 1x RJ11 v.90/92 Modem 1x15 pin RGB External Monitor Output 1x Composite Analog Video Input Port 1x DC Input 1x Shrouded Hot-docking Port 1x RJ-45 10/100/1000 Base-TLAN 2x External RF Pass-Through Ports (1:GPS, 1:WWAN)
Battery	Smart Li-Ion 7200 mAh Secondary Battery (Media Bay Option) 3500 mAh
AC Adapter	Universal AC adapter – Input: 100-240 V, 50/60 Hz AC

PHYSICAL

Dimensions	3.2" x 11.1" x 13.2" (336mm x 283mm x 78mm)
Weight	9.8 lbs (4.5 kg)
Operating System	Microsoft® Windows Vista™ Business Edition, SP1 (32 bit), with downgrade rights to Windows® XP Professional, SP2

SPECIFICATION SHEET

ML910™
Rugged Notebook

ENVIRONMENTAL STANDARDS (MAIN SYSTEM)

Temperature	According to IEC 68-2-1,2,14 / MIL-STD-810F, Method 501.4, 502.4 Operating: -20°C to 60°C (Tested)
Humidity	According to IEC 68-2-30 / MIL-STD-810F, Method 507.4 5% to 95% RH, non condensing
Altitude	According to IEC 68-2-30 / MIL-STD-810F, Method 500.4 Operating: 15,000 ft Non-operating: 40,000 ft altitude change rate: 2,000 ft/min
Drip	According to MIL-STD-810F, Method 506.4
Shock	According to IEC 68-2-27 / MIL-STD-810F, Method 516.5 Operating: 20g, 11 ms, half sine wave Non-operating: 50g, 11 ms, half sine wave
Vibration	According to IEC 68-2-6 / MIL-STD-810F, Method 514.5 Operating: 10~55Hz/0.075mm, 55~500Hz/1.0g Non-operating: 10~55Hz/0.15mm, 55~500Hz/2.0g
Dust	According to MIL-STD-810F, Method 510.4 5 hours in dust-laden atmosphere
Drop	According to IEC 68-2-32 / MIL-STD-810F, Method 516.5 (base unit only) Survives 30-36" drop depending on configuration
Enclosure	According to IEC 60529 IP54 (Ingress Protection rated "5" for dust and "4" for splashing water), NEMA, MIL-STD-810F, Method 506.4, 510.4
Regulatory	FCC part 15, Subpart B, Class B, UL, CE, IC
Integrated Wireless Communication Options	1x Wide Area RF (Private DataTAC or EVDO (RevA)/1xRTT or GPRS/Edge/UMTS) (optional) 1x Wireless LAN (802.11abg with LEAP) Standard 1x Global Positioning System (GPS) receiver (Trimble Lassen iQ GPS Module) (optional) 1x Personal Area Network (Bluetooth) Standard RF Pass-through with external Antennas for Wide Area Network and GPS (optional) when Docked in High-Tier Docking Station
Accessories and Options	Primary and Secondary Batteries Office Port Replicator/Docking Station Vehicle Docking Station (High-Tier, Mid-Tier) External Mounted GPS and WWAN antennas DC 12V Cigarette Lighter Adapter USB Floppy Disk Drive (External) Configurable Media Bay Options: CD RW / DVD ROM (Combo Drive), CD RW/ DVD RW (Dual Drive), or Secondary Battery. PCMCIA Smart Card Reader PCMCIA Motorola Mesh Modems (WMC 6300, WMC 7300, WDE 1000) Mobile Office Display Solution (MODS: for functional dual display in-vehicle use)
Warranty	3 Year Full Warranty Standard (1 Year Consumables, e.g. batteries) Extended Service Plans Available

SPECIFICATION SHEET

ML910™
Rugged Notebook



MOTOROLA

Motorola, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. www.motorola.com/ML910 1-800-367-2346

MOTOROLA, MOTOMESH, DataTAC and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. Intel® is a trademark or registered trademark of Intel Corporation or its subsidiaries in the United States and other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation; and Windows XP and Windows Vista are trademarks of Microsoft Corporation. All other product or service names are the property of their registered owners. The Bluetooth trademarks are owned by their proprietor and used by Motorola, Inc. under license. © Motorola, Inc. 2008 All rights reserved.

R3-14-2050D (0810)



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.


Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health




Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service