

Product profile

IP30

Handheld RFID Reader



- Easy snap-on installation to Intermec mobile computers featuring GPS or near/far area imaging
- Light-weight ergonomic design with choice of Bluetooth® or USB connection
- Seamless application portability between Intermec fixed readers and IP30
- Optional non-incendive (NI) configurations
- Based on EPCglobal certified radio
- Available in 869MHz or 915MHz frequency bands for global operation

The Intermec IP30 add-on passive UHF RFID handle is a cost-effective, compact, EPCglobal-certified solution for adding mobile RFID read/write capability to Intermec's latest generation of mobile computers including the CN3, CN3e, CK61 and CK61ex.

The modularity of the IP30 and the RFID-readiness of the Intermec mobile computers mean the power of RFID can be literally added in a snap today or at any point in the future to support both in-premise and in-field applications such as warehouse operations, enterprise asset management, in-transit-visibility, direct store delivery and exception handling.

When combined with Intermec's most powerful mobile computers, the CN3 and CN3e, the IP30 gives the user unmatched data collection and communication capabilities. Combining integrated RFID and GPS, along with WiFi, Bluetooth® and WWAN, into a single handheld computer enables pin-point location accuracy for real-time asset, source and service tracking.

The combination of the IP30 and Intermec's new CK61ex mobile computer offer investment protection for the supply chain of tomorrow. Increasingly RFID and bar code labeling are moving away from simple "either-or" co-existence toward

complementary solutions that marry identification at the item, case and pallet levels. The IP30 and CK61ex deliver the needed flexibility to not only read RFID, but also 1D and 2D bar codes from any angle, near or far, within the same application.

When harsh and hazardous environments make RFID one of the only viable identification and data collection methods, the non-incendive rated version of the IP30, combined with the CK61NI mobile computer and Intermec's rigid RFID tags, provides a certified device for reading and writing to RFID tags and transmitting the data via wireless LAN.

Similar to Intermec's industry leading fixed and vehicle mount RFID readers, the IP30 has an EPCglobal certified radio that enables seamless application portability among all RFID applications using Intermec readers.

SmartSystems™ Foundation, standard on the Intermec mobile computers, provides a single, convenient console for quick set-up and configuration of all of the settings contained in the device. Administrators can change device settings, send firmware upgrades, update software applications, and execute other changes directly from the console to save time and cut costs.

The IP30 Handheld RFID Reader is based on Intermec's IM4 radio module.

Physical Description

The IP30 handheld reader incorporates the Intermec IM4 radio module as well as a linear polarized antenna. The IP30 supports both Bluetooth and USB connection to Intermec's CN3, CN3e, CK61 and CK61ex mobile computers. The IP30 meets both ETSI and FCC standards. It can be factory configured to operate in RFID frequency bands: 869MHz, 915MHz.

Physical Characteristics

Weight without handheld computer:

430 grams with battery (15.4 oz)

Weight with CN3:

860 grams with battery (1.9 lbs)

Weight with CK61:

1.16 kg with battery (2.55 lbs)

Environment

Operating Temp: 0° C to 50° C (32° F to 122° F)

Storage Temp: -30° C to 70° C (-22° F to 158° F)

Humidity: 10 to 95% (non-condensing)

Enclosure: IP64 compliant

Shock: 30 G, 11 ms, half sine pulse (operating)

Vibration: Quasi Random Vibration 17.5G RMS

for 2 hours, each of three axis

Drop Survival: Withstands 4 foot drop (1.3m)

26 times to concrete

Non-incendive (NI) Option: Class I - Div. 2 Groups A, B, C, D; Class II - Div. 2 Groups F, G; Class III - Div 2. T4 (Certification Pending)

Compatible Handheld Computers

CN3, CN3e, CK61, CK61ex

Standard Features

Communications Interface

Bluetooth and USB configurations

Antenna

Linear polarized

Field

70-degree cone (approx.) measured from nose of device

Typical Read Range (tag dependent)

6.09 cm to 304.8 cm (0.2 ft. to 10 ft.)

Typical Write Range (tag dependent)

30.5 cm to 60.9 cm (1 ft. to 2 ft.)

Output Power

U.S. -1W (4W EIRP); Europe - .5W

Indicator LEDs

Five indicator LEDs:

1. SmartSystems - Power/Ready to Work
2. Data Transfer to Host
3. RF on
4. Tag Read
5. Battery Status

Power

Removable Lithium-ion battery pack

Accessories

External battery charger

RFID Frequency Ranges

869 and 915 MHz

Tag Air Interfaces

EPCglobal UHF Gen 2

ISO 18000-6b

ISO 18000-6c

North America

Corporate Headquarters

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

South America & Mexico Headquarters Office

Newport Beach, California
Phone: (949) 955-0785
Fax: (949) 756-8782

Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific Headquarters Office

Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
FreePhone ROW: 00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799



Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611867-01A 01/08

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.





www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service