



1166 / 1266



1166 / 1266

Wireless Scanners

Wireless, comfortable, and easy to use, CipherLab Bluetooth scanners give you a flexible data-capture tool that makes work faster and more efficient. CipherLab 1166 and 1266 Bluetooth Class 2 compliant scanners give workers greater mobility and freedom to go where the work is and get it done fast.

# 1166 / 1266

Wireless Scanners



## Keep business moving

Improve speed and accuracy of inventory and manufacturing functions, including picking and packing, WIP, and paperless accounting. Wireless scanning with the 1166/1266 Bluetooth scanners keeps parts and processes on track. In the warehouse or on the manufacturing line, these scanners travel with you, capturing critical data. Even if the scanner is outside its extended 100-meter range, captured data is automatically uploaded to your server when connection with the host device is regained, giving near limitless flexibility with greater business accuracy.

## Keep customers happy

Nobody likes waiting in line. CipherLab 1166/1266 wireless scanners let you take the scanner to the customer, speeding check-out for many products, especially bulky items. CipherLab Bluetooth scanners help speed customers on their way. And that makes everyone happy.

## Improve patient care

Whether checking patients into the hospital, inventorying and distributing medications, or documenting doctors' rounds, our 1166/1266 wireless scanners make it easier to get jobs done with greater accuracy and responsiveness. Instead of fitting daily processes to a technology, Bluetooth Class 2 compliant connectivity gives caregivers greater mobility and flexibility to adapt the scanner to the way they work—enhancing communications between doctors, nurses, labs, and pharmacies.

## Smart solutions with immediate payoffs

### Streamline tracking and delivery

*To improve tracking and delivery of mail and goods, Brazil's ECT, the largest post office in Latin America, uses CipherLab 1166 scanners.*



ECT combined 4,010 CipherLab 1166 scanners with middleware developed by Compex to scan packages as they arrive and depart ECT offices. Working up to 24 hours a day, the scanners wirelessly communicate with ECT databases. Updated with incoming and outgoing activities, ECT maintains a high level of service quality and customer trust with improved operations management.

### Improve stocking while boosting image

*CERRUTI 1881, a leading international designer and retailer of fashion products, chose CipherLab 1266 scanners for its POS systems.*



CipherLab 1266 scanners were installed at all its 300 point-of-sale terminals to help CERRUTI 1881 deliver a modern, state-of-the-art retail image to its customers while streamlining stocking control. The 1266 scanners help ensure store shelves stay stocked with the upscale products customers demand most.

### Real-time stocking update

*ASDA/Wal-Mart Stores in UK use CipherLab 1266 scanners to manage CD and DVD stocking.*



After searching worldwide for scanners with the right communications capabilities for a new replenishment system for CDs and DVDs, ASDA/Wal-Mart purchased 200 1266 Bluetooth scanners from a CipherLab distributor in the UK. Store personnel read product barcodes with 1266 scanners and stocking requirements are instantly relayed via Bluetooth to smart mobile phones or PDAs, supplying real-time stocking data to the distribution center.

# 1166/1266

Wireless Scanners



## A powerful scanner without limitations

### NEVER MISS A BARCODE

With a range of 100 meters, the 1166 and 1266 can go a long way to wirelessly scan barcodes. Out of range? The reserve buffer automatically captures up to 256 scans and transmits them to your host device when back in range. Or work offline with preset batch mode and store up to 8,192 scans in flash data memory for upload later.

### ALWAYS AVAILABLE TO WORK WITH YOU

CipherLab's energy-efficient design keeps our Bluetooth scanners working long hours—up to 45 hours or 32,000 scans on a single charge—staying as productive as your workers.

### SHARE A CRADLE FOR COST EFFICIENCY

The 3666 cradle communicates with up to seven scanners, adding full Bluetooth Class 2 compliant capabilities to any server. This allows you to run multiple simultaneous operations without the added expense of additional cradles, optimizing your low total cost of ownership on an already flexible, durable scanner.

### BUILT FOR RUGGED ENVIRONMENTS

Our 1166/1266 scanners were designed to handle the harsh environments found in manufacturing, warehouses, and other hard-working facilities. Built of sturdy plastic and rubber, they withstand multiple drops onto concrete and operate in a wide range of temperatures and humidity.

### SMART TECHNOLOGY

The 1166 and 1266 scanners support multiple interfaces besides Bluetooth to upload data, including RS-232, keyboard wedge, virtual COM, and human interface device (HID). They communicate with any host with a Bluetooth Class 2 compliant profile, giving you maximum flexibility to communicate with notebook PCs, printers, PDAs, and other devices—even mobile phones.



## CipherLab—the wireless scanner pioneer

CipherLab pioneered wireless scanners, enabling users to work smarter and faster. With such an innovative breakthrough in scanning, users have been able to serve retail customers quicker, improve productivity in manufacturing environments, and help raise the level of patient care and hospital efficiency.

CipherLab's early introduction of Bluetooth Class 2 compliant scanners is another example of the company's continuing industry leadership with high-quality, rugged scanners that are designed to meet the specific needs of users in a wide range of environments. Our products are recognized around the world for their work and business value:

- ▶ **RANKED IN TOP FIVE BY RESELLERS** In 2006, *Vertical Systems Reseller*, a leading United States AIDC magazine, rated CipherLab among the top five scanner manufacturers.
- ▶ **RATED IN TOP THREE WORLDWIDE** In a *Venture Development Corporation* 2006 survey, end users ranked CipherLab in the top three best handheld scanners.
- ▶ **CIPHERLAB SCANNER USED BY MILLIONS WORLDWIDE** CipherLab scanners lead worldwide sales with a reputation for quality and reliability.

CIPHERLAB PRODUCTS ARE  
VALUED WORLDWIDE FOR  
ENGINEERING EXCELLENCE.  
OUR **WIRELESS SCANNERS**  
ARE ANOTHER EXAMPLE OF  
TECHNICAL INNOVATION AND  
QUALITY VALUE FOR TODAY'S  
AIDC SOLUTIONS.

# SPECIFICATIONS

## 1166 / 1266

### Wireless Scanners



1166



1266

|                  |                                                                                                                            |                                                                                                                                                                                                                             |                                      |
|------------------|----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| RF communication | Module                                                                                                                     | BT Class 2 compliance                                                                                                                                                                                                       |                                      |
|                  | Coverage (line of sight)                                                                                                   | 100 m / 328 feet                                                                                                                                                                                                            |                                      |
|                  | Standard profile                                                                                                           | SPP, HID or through 3666 base                                                                                                                                                                                               |                                      |
| Performance      | Optical sensor                                                                                                             | 3648 pixels                                                                                                                                                                                                                 | Laser                                |
|                  | Light source                                                                                                               | Red LED 630 nm                                                                                                                                                                                                              | Visible laser diode at 650±15 nm     |
|                  | Resolution                                                                                                                 | 4 mil                                                                                                                                                                                                                       |                                      |
|                  | Depth of field<br>depends on barcode resolution                                                                            | 2 to 33 cm / 0.8 to 13 in.                                                                                                                                                                                                  | 1 to 63 cm / 0.4 to 24.8 in.         |
|                  | Scanning angle                                                                                                             | Pitch ±70° Skew ±70°                                                                                                                                                                                                        |                                      |
|                  | PCS                                                                                                                        | Minimum 45%                                                                                                                                                                                                                 |                                      |
|                  | Scan rate                                                                                                                  | 100 scans/second                                                                                                                                                                                                            |                                      |
|                  | Interfaces supported                                                                                                       | RS232 / Keyboard wedge / USB HID                                                                                                                                                                                            |                                      |
|                  | Barcodes supported                                                                                                         | Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, MSI, Plessey, Telepen, UPC-A, UPC-E, EAN-8, EAN-13, GS1-128(EAN-128) |                                      |
|                  | Programmable features                                                                                                      | Data editing, interface selection, symbology configuration                                                                                                                                                                  |                                      |
|                  | Language support                                                                                                           | US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German                                                                                                                                |                                      |
| Physical         | Weight including battery                                                                                                   | 200 g / 7.1 oz.                                                                                                                                                                                                             | 210 g / 7.4 oz.                      |
|                  | Color                                                                                                                      | Dark grey                                                                                                                                                                                                                   |                                      |
|                  | Switch                                                                                                                     | Micro switch                                                                                                                                                                                                                |                                      |
| Electrical       | Voltage                                                                                                                    | DC 5V ±5% (with adapter) / 3.7V 700 mAh Li-ion battery                                                                                                                                                                      |                                      |
|                  | Power consumption<br>Standby / Scanning / Maximum                                                                          | 12 mA / 170 mA / 250 mA                                                                                                                                                                                                     | 12 mA / 85 mA / 150 mA               |
| User environment | Temperature                                                                                                                | Operating: 0° to 50°C / 32° to 122°F                                                                                                                                                                                        | Storage: -20° to 60°C / -4° to 140°F |
|                  | Humidity Non-condensing                                                                                                    | Operating: 10% to 90%                                                                                                                                                                                                       | Storage: 5% to 95%                   |
|                  | Impact resistance                                                                                                          | Withstands multiple 1.2 m / 4 ft. drops onto concrete                                                                                                                                                                       |                                      |
|                  | Electrostatic discharge                                                                                                    | Conforms to ±15 kV air discharge and ±8 kV contact discharge                                                                                                                                                                |                                      |
|                  | EMC regulation                                                                                                             | CE, C-Tick, FCC, IC, TELEC                                                                                                                                                                                                  |                                      |
| Configuration    | Setup options include Windows®-based ScanMaster software (included), by direct connection or printing out barcode settings |                                                                                                                                                                                                                             |                                      |
| Accessories      | Charging cradle and charging/communication cradle                                                                          |                                                                                                                                                                                                                             |                                      |
| Warranty         |                                                                                                                            | 3 year                                                                                                                                                                                                                      | 3 year (laser engine 1 year)         |



**Charging/Communication Cradle**  
Simultaneously communicates with up to seven 1166/1266 scanners

©2011 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.



**HEADQUARTERS**  
CipherLab Co., Ltd.  
12F, 333 Dunhua S. Rd., Sec.2  
Taipei, Taiwan 10669  
Tel +886 2 8647 1166  
Fax +886 2 8732 3300  
www.cipherlab.com

**CipherLab China**  
J Room, 4F, No.728 West Yan'an  
Road, Changning District, Shanghai  
China 200050  
Tel +86 21 3368 0288  
Fax +86 21 3368 0286

**CipherLab USA**  
2552 Summit Avenue  
Plano, Texas USA 75074  
Tel +1 469 241 9779  
Toll Free 888 300 9779  
Fax +1 469 241 0697

**CipherLab Central Europe**  
Willicher Damm 143-145  
41066 Mönchengladbach  
Germany  
Tel +49 2161 56230 0  
Fax +49 2161 56230 22



[www.logiscenter.com](http://www.logiscenter.com)  
902 050 030



[www.logiscenter.it](http://www.logiscenter.it)  
02 479 216 97



[www.logiscenter.de](http://www.logiscenter.de)  
info@logiscenter.de



[www.logiscenter.pt](http://www.logiscenter.pt)  
308 800 842

## About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permanent stock of more than 12,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.


**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.

## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health




Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables  
(labels, ribbons, PVC cards)

## Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands  
Technical Service