

Specifications

Model	CT-P291	CT-P293	CBM-920 II
Printing method	Line thermal dot printing		Serial dot impact
Printing width	54mm, 432 dots	72mm, 576 dots	57.5mm
Printing speed	Max. 150mm/sec		24 col = 2.5 lines/sec
Number of columns	Font A: 34 columns Font B: 45 columns Font C: 51 columns	Font A: 48 columns Font B: 64 columns Font C: 72 columns / Max 54 columns	24/40 columns
Character size (WxH)	Font A: 1.25 x 3.00mm (12 x 24 dots) Font B: 0.88 x 2.13mm (9 x 17 dots) Font C: 1.00 x 2.00mm (8 x 16 dots)		24 col = 1.62 x 2.4mm 40 col = 1.08 x 2.4mm
Dot pitch/Character pitch	24 col = 1.98mm		24 col = 1.98mm 40 col = 1.19mm
Barcode type	UPC-A/E, JAN (EAN)-13/8 columns, ITF, Code 39, Code 128, CODABAR, CODE 93, PDF417, QR Code		
Line spacing	4.25mm (1/6 inch); can be set by a command.		Character = 3.52mm Graphic 2.4mm
Paper	58 x Max. Ø50mm	80 x Max. Ø50mm	57.5
Interface	Parallel (Centronics), Serial (RS-232C), USB		Parallel (Centronics), Serial (RS-232C)
Input buffer	4K bytes / 45 Bytes		2k bytes
Power supply	Input voltage: DC24V ± 10%, Current consumption: 1.9A (9A at peak)		DC/V
Weight	Approx. 700g	Approx. 800g	0.47kg
Dimensions (W x D x H)	107x120.5x109 mm	127x120.5x109 mm	106x180x88mm
Operating temp. ranges	-20~50°C, 10 to 85%RH (No condensation)		0 to 40°C
Storage temp. range	-20~60°C, 10 to 90% RH (No condensation)		-20 - 60°C
Reliability	Thermal head 100,000,000 pulses or 100 KM Auto cutter 1 million cuts		Printer: 1.5 million lines
EMC and safety standards	UL, C-UL, FCC class A, TÜV-Bauart, CE marking		FCC class B

Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

Type Classification

CT-P291 AL U WH NN
1) 2) 3) 4) 5)

CBM-920II-24 R F 230
1) 2) 3) 4) 5)

1) **Model type**
CT-P291 (58mm)
CT-P293 (80mm)

2) **Interface**
AL: (Serial + Parallel + USB)

3) **Market**
U: (international)

4) **Body case colour**
WH: White

5) **Wiring cable**
NN: standard harness type
DC: Hoshiden connector type

1) **Model type**
CBM-920 Type II

2) **Number of columns**
24: 24 columns/144 dots
40: 40 columns/180 dots

3) **Interface**
P: Parallel (Centronics)
R: Serial (RS-232C)

4) **Character set**
F: International

5) **Power source**
DC: DC 5V

Features

CT-P291/CT-P293

- Compact design
- Panel mounting
- 150 mm/sec. printing speed
- Easy drop-in paper loading
- 1D and 2D barcode printing
- ESC/POS compatibility
- Auto cutter
- Low temperature operation down to -20°C
- Splash-proof design (JIS Class 1)
- DC 24V drive
- Parallel, serial and USB interface



CBM-920 II

- Palm size and Light weight
- Bit image graphics printing
- Memory switch function
- 2K bytes input buffer
- Panel mount
- Paper-near-end sensor
- Paper auto loading
- Paper-end sensor

