

Getac

Rugged Mobile Computing Solutions

V200

Fully Rugged Convertible Notebook

- 3rd Generation Intel® Core™ i7 / i5 vPro™ Processor
- 12.1" Getac QuadraClear® Sunlight Readable Display: 1200 Nits with Touchscreen
- LifeSupport™ Battery Swappable Technology
- Integrated SiRFstarIV™ High Sensitivity GPS and 3.5G WWAN
- Optional Dual Mode Touchscreen (multi-touch and digitizer)



Vehicle Dock



Office Dock



Rugged Mobile Computing Solutions

V200 Fully Rugged Convertible Notebook

Getac recommends Windows.



Specifications

Operating System	Windows® 7 Professional	Communication Interface	10/100/1000 base-T Ethernet 56K ITU V.92 modem Intel® Centrino® Advanced-N 6235; 802.11 a/b/g/n Bluetooth (v4.0 class 1) Optional SiRFstarIV™ GPS Optional Gobi™ mobile broadband
Mobile Computing Platform	Intel® Core™ i7 vPro™ Technology - Intel® Core™ i7-3520M vPro™ Processor 2.9GHz, Max 3.6GHz, with Intel® Turbo Boost Technology - 4MB L3 Intel® Smart Cache - Mobile Intel® QM77 Express chipset Intel® Core™ i5 vPro™ Technology - Intel® Core™ i5-3320M vPro™ Processor 2.6GHz, Max. 3.3GHz with Intel® Turbo Boost Technology - 3MB L3 Intel® Smart Cache - Mobile Intel® QM77 Express chipset	Software	Getac Utility Getac Camera Getac V-GPS Adobe® Reader®
VGA Controller	Intel® HD Graphics 4000 ⁱ	Security Feature	Intel® vPro™ Technology TPM 1.2 Optional fingerprint scanner Optional smart card reader Kensington lock
Display	12.1" TFT LCD WXGA (1280 x 800) 1200 nits QuadraClear® sunlight readable display with multi-touch screen	Power	AC Adapter (90W, 100-240VAC, 50 / 60 Hz) Li-Ion smart battery (8700mAh) (up to 14 hours of battery life) ⁱⁱ Optional Li-Ion smart battery (6140mAh) Optional LifeSupport™ battery swappable technology ⁱⁱⁱ
Storage & Memory	4GB DDR3 expandable to 8GB SATA HDD 500GB Optional SATA SSD 128 / 256GB	Dimension (W x D x H) & Weight	314 x 222 x 49 mm, 2.7 kg ^{iv}
Keyboard	Membrane keyboard Optional LED backlit membrane keyboard Optional LED backlit rubber keyboard	Rugged Feature	MIL-STD-810G certified and IP65 certified MIL-STD-461F certified ^v Optional ANSI/ISA 12.12.01 Full magnesium alloy case Shock-protected removable HDD Vibration & drop resistant Optional night vision
Pointing Device	Touchscreen - Pressure sensitive multi-touch screen - Optional dual mode touchscreen (multi-touch and digitizer) Touchpad - Glide touchpad with scroll bar	Environmental Specification	Temperature ^{vi} : - Operating: -20°C to 60°C - Storage: -51°C to 71°C Humidity: - 95% RH, non-condensing
Expansion Slot	PCMCIA Type II x 1 ExpressCard/54 x 1 Optional smart card reader (occupies one PCMCIA Type II slot) x 1 SD card reader x 1	Optional Accessories	Carry bag Battery charger Vehicle adapter (90W, 11-16VDC and 22-32VDC) MIL-STD-461F certified AC adapter (90W, 100-240VAC) Digitizer stylus Stylus and tether Protection film X strap Main battery (8700mAh) / Lightweight battery (6140mAh) AC adapter (90W, 100-240VAC) Vehicle dock Office dock
I/O Interface	2M pixels webcam x 1 Serial port (9-pin; D-sub) x 1 External VGA (15-pin; D-sub) x 1 Microphone (Mini-jack) x 1 Audio output (Mini-jack) x 1 DC in Jack x 1 USB 3.0 (9-pin) x 2 USB 2.0 (4-pin) x 1 Modem (RJ11) x 1 LAN (RJ45) x 1 IEEE 1394a x 1 Docking connector (100-pin) x 1 Optional RF antenna pass-through for GPS, WLAN and WWAN		

Docking Solutions

	Dimension (W x D x H)	Serial Port	External VGA	Microphone	Audio Output	DC in Jack	USB	LAN	Video Capture	Parallel Port	RF Antenna Connector
Vehicle Dock	275 x 298 x 97 mm (10.8" x 11.7" x 3.8")	2	Optional	1	1	1	4	1	1	--	3 (WWAN, WLAN, GPS)
Office Dock	310 x 120 x 45mm (12.2" x 4.7" x 1.8")	1	1	1	1	1	4	1	--	1	--

i Share memory size may vary by different operating system and RAM size.

ii Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

iii The system will stay operating (within 120 seconds in standby mode) when user swaps the battery.

iv Weight varies from configurations and optional accessories.

v MIL-STD-461F 90W AC adapter sold separately

vi Tested by a national independent third party test lab following MIL-STD-810G

Getac



Getac Technology Corporation

Mitac house, Nedge Hill, Telford,
Shropshire, TF3 3AH, U.K.
Tel: +44 1952 207 231
sales-getac-UK@getac.com
www.getac.co.uk

Copyright © 2013 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
All specifications are subject to change without notice. V03M10Y13UK



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service