XT8300 Series



XT8317
17" Display | 1280 x 1024

XT8315
15" Display | 1024 x 768



KEY FEATURES

- Intel® Tiger Lake Core i3-1115G4 (1.70GHz base frequency, up to 4.1GHz by Intel® Turbo Boost Technology) 6MB Intel® Smart Cache;
  Intel® Tiger Lake Core i5-1155G7 (1.0GHz base frequency, up to 4.5GHz by Intel® Turbo Boost Technology), 8MB Intel® Smart Cache
- 15" or 17" display
- 2x slots 4GB DDR4 SO-DIMM (Max. 64GB)
- Projected Capacitive touch
- Sleek, folding base design
- Slimmer overall footprint
- Optional Upgrade Kits
  - Powered USB and USB Hub Expansion Kit
    - PU490 Hub
      - (1) 24V Powered-USB Port
      - (3) 12V Powered-USB Ports
      - 150W Power Adapter
    - PU480 Hub
      - (1) 24V Powered-USB Port
      - (8) Standard USB 2.0 Ports
      - 150W Power Adapter

Power and Performance

The XT8300 models are a part of the XT Series, built with a practical and durable design. The XT8300 Series is carefully thought out to make itself one of the most visually desirable terminals in the market.

And, with a patented foldable base, users can adjust the screen to a height and angle of their choice, providing unparalleled flexibility.

With its fanless design, the XT8300 requires less maintenance and can run silently, which is ideally suited for high-end boutique stores or hospital environments.

XT8300 Series

Specifications	XT8315	XT8317
Processor Options	- Intel® Tiger Lake Core i3-1115G4 (1.70GHz base frequency, up to 4.1GHz by Intel® Turbo Boost Technology) 6MB Intel® Smart Cache - Intel® Tiger Lake Core i5-1155G7 (1.0GHz base frequency, up to 4.5GHz by Intel® Turbo Boost Technology), 8MB Intel® Smart Cache	
System Memory	2x slots 4GB DDR4 SO-DIMM (Max. 64GB)	
TPM Support	TPM 2.0	
Storage Device	M.2 128GB SSD or higher. Up to two drives.	
Supported OS	Windows 10 IoT Enterprise LTSC 64bit	
Passive Cooling	Fanless	
Touch	True-Flat Projected Capacitive with Multi-touch support	
Physical Dimensions		
Dimensions (WxDxH) in.	14.6 x 12.6 x 10	15.9 x 9.8 x 13.9
Display	15" (1024 x 768)	17" (1280 x 1024)
Weight (lbs)	12.9	15.8
Connectivity		
LAN Port	2 x Gigabit LAN	
Serial Port	3 x RJ-50 Serial (5v/12v support on all COM ports 1-3)	4 x RJ-50 Serial (5v/12v support on COM ports 1-3)
Display Port	1x VGA Port (12v Support for Posiflex monitors) + 1 x HDMI	
USB Port	2 x USB 2.0; 4 x USB 3.0	4x USB 2.0; 4 x USB 3.0
12v Battery Port	1 x Proprietary port used with RB2000	
Expansion Slot	WiFi	
CR Port	1 Port (Controls 2 Drawers); Dual Independent Open Sensor; COM1/COM5 Select; 24v Support	
Options		
SSD	M.2 SSD	
Parallel Port	Parallel Port with optional extension cable	
Wall Mount	WB-5000 wall mount bracket	
VESA Mount	100mm	
WiFi/Bluetooth	M.2 802.11ac, Dual Band 2.4GHz / 5GHz; BT 4.2	
Powered USB	1 x 24V + 3 x 12V (via GEN8E base)	

** The product information and specifications are subject to change without prior notice.







SECONDARY DISPLAYS	MAGNETIC STRIPE READERS	CASH DRAWERS	RECEIPT PRINTER
 PD2608 PD2605 LM3010 Bezel-Free Rear Mount	 SA100 SA300 Optional: Fingerprint Reader	 CR3100 Adjustable Coin Slot CR6300 Fixed Coin Slot	 PP9000 PP7600

Posiflex designs, engineers and manufactures:

Touch Screen Terminals | Tablets | Kiosks | Printers | Magnetic Stripe Readers | Cash Drawers | Rear/Pole Displays

POSIFLEX™

Posiflex Business Machines, Inc.
30689 Huntwood Ave.
Hayward, CA 94544
P: 888-968-1668
F: 510-475-0982
sales.department@posiflexusa.com
www.posiflexusa.com

Rev. 111524