

CODE READER™ 1000

Compact, efficient and powerful, this is advanced technology at a maximum value.

Weighing in at just 2.4 oz, capable of withstanding multiple drops from 6 feet and able to work at 131° F, the simple and intuitive CR1000 could be the toughest featherweight you'll ever meet. It quickly and reliably decodes 1D, 2D and Postal bar codes from any surface type. Featuring Code's Affinity rapid disconnect cable set, you can count on durable connectivity between reader and host device, with the ability to quickly remove and replace damaged cables. For data editing and parsing, end users can leverage it's JavaScript platform to create custom routines and applications that are easily embedded into the reader.

Advanced data management and excellent versatility.

In retail applications, the CR1000 excels in and can be combined with various peripherals for a truly unique point-of-sale solution. From mobile devices like workstations-on-wheels, tablet PCs or environmentally conscious kiosk operators, the CR1000 works on a large scale in a limited workspace.

For intuitive, lightning fast performance that won't drain your battery or your budget, choose the CR1000.

Features & Benefits

- High speed, omnidirectional reading of 1D, 2D and Postal bar codes
- Manual or automatic triggering
- Bright LED indicator and loud, programmable tone indicator
- Reads bar codes on mobile devices
- Compatible with Code's CortexTools™ software configuration utility
- Data editing and parsing with JavaScript
- Uses Code's rapid disconnect Affinity® cables
- Extremely efficient power consumption (lowest in its class)
- Optional stand
- Disinfectant-ready IP54 housing
- Available in light and dark gray

Applications

Healthcare, mobile coupon or ticketing, pharmacy, patrol vehicles, ATMs or kiosks, retail, and manufacturing

Features at a glance



CODE READER™ 1000 SPECIFICATIONS

Physical Characteristics

CR1000 Dimensions	1.7" H x 2.6" L x 2.2" W (30 mm H x 67 mm L x 52 mm W)
CR1000 Weight	2.4 oz (68 g)
Color Options	Available in light or dark gray
IP Rating	54

User Environment

Operating Temperature	-20° to 55° C / -4° to 131° F
Storage Temperature	-30° to 65° C / -22° to 150° F
Humidity	5% to 95% non-condensing
Decode Capability	1D: Interleaved 2 of 5, GS1 DataBar (RSS), Hong Kong 2 of 5, Maxtrix 2 of 5, MSI Plessey, Pharmacode, Plessey, Straight 2 of 5, Telepen, Trioptic, UPC/EAN/JAN Stacked 1D: GS1 Composite (CC-A/CC-B/CC-C), MicroPDF, PDF417 2D: Aztec Code, Data Matrix, Micro QR Code, QR Code, Han Xin Proprietary 2D: GoCode® (Additional License Required) Postal Codes: Australian Post, Intelligent Mail, Japan Post, KIX Code, PLANET, POSTNET, UK Royal Mail
Image Output Options	Formats: JPEG or PGM
Field Selection	High Density or Wide Field
Data Editing	JavaScript (Additional License Required)

Working Ranges

CR1000 Performance

Test Code	Min Inches (mm)	Max Inches (mm)
3 mil Code 39	3.1" (80 mm)	4.0" (102 mm)
7.5 mil Code 39	1.3" (33 mm)	7.2" (182 mm)
10.5 mil GS1 DataBar	0.8" (20 mm)	8.7" (220 mm)
13 mil UPC	1.1" (28 mm)	11.0" (280 mm)
4.2 mil DM	1.9" (48 mm)	4.3" (110 mm)
5 mil DM	1.7" (43 mm)	4.5" (115 mm)
6.3 mil DM	1.3" (33 mm)	5.9" (150 mm)
10 mil DM	0.8" (20 mm)	7.1" (180 mm)
20.8 mil DM	1.1" (28 mm)	13.5" (343 mm)

Note: Working ranges are a combination of both the wide and high density fields. All samples were high quality codes and were read along a physical center line at a 10° angle. Default AGC settings were used. Accuracy= +/- 10%.

Performance Characteristics

Field of View	High Density Field: 30° horizontal by 20° vertical Wide Field: 50° horizontal by 33.5° vertical
Focal Point	High Density Field: approximately 100 mm Wide Field: approximately 115 mm
Sensor	CMOS 1.2 Megapixel (1280 x 960) gray scale
Optical Resolution	High Density Field: 960 x 640 Wide Field: 960 x 640
Pitch	± 60° (from front to back)
Skew	± 60° from plane parallel to symbol (side-to-side)
Rotational Tolerance	± 180°
Print Contrast Res.	25% (1D symbologies) or 35% (2D symbologies) absolute dark/light reflectance differential, measured at 650 nm
Target Beam	Single, blue targeting bar
Ambient Light Immunity	Sunlight: Up to 9,000ft-candles/96,890 lux
Shock	Withstands multiple drops of 6' (1.8 Meters to concrete)
Power Requirements	Reader @ 5vdc (mA): Typical = less than 450 mA; Idle = less than 80 mA; Sleep = less than 31 mA
Memory Capacity	128MB Flash ROM, 32MB RAM
Communication Interfaces	RS232, USB 2.0 (Generic HID, HID Keyboard, Virtual Com Port)
Warranty	2 year standard warranty; extended service plan available

Accessories

- Various Cable Options Available.
Visit www.codecorp.com/cables.php
for a list of compatible cables
- Universal Stand



code
ADVANCED BAR CODE READERS

Phone: (801) 495-2200
Web: www.codecorp.com



800 729 0236
www.logiscenter.us



0241 9550 9225
www.logiscenter.de



01 82 88 44 70
www.logiscenter.fr



020 3318 8265
www.logiscenter.co.uk



0720 115814
www.logiscenter.at



02 58 80 583
www.logiscenter.be



911 433 048
www.logiscenter.com



02 4792 1697
www.logiscenter.it



308 800 842
www.logiscenter.pt

About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 60,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.



All Brands Technical Service


Our Brands




Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers




Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)