

Falcon® 4410

Windows® Based Mobile Computer



At A Glance

"I never knew a brick device could be so light. The 4410 is a winner in my distribution center. Between the variety of scan engines, Laser and Imaging, there is a configuration for every need we have."

— Warehouse Manager, PSC Warehouse Customer



Accessories

- Powered Vehicle Mount Dock
- Single-Slot and Four-Slot Dock
- Four-Slot Battery Charger
- Optional Handle Conversion Kit
- Holsters/Softcases
- USB Data Cable
- Serial Charging Cable
- Serial Printer Adapter
- Extended Warranty
- Service Options

Alternative PSC Solutions

- Falcon® 4420 Mobile Computer
- Falcon® 4220 PDA
- Falcon® 5500 Hybrid Computer

FEATURES	BENEFITS
Ergonomic and Durable Design	• The lightweight form factor fits comfortably in the user's hand and reduces fatigue during long duration usage. • Rugged design survives multiple 5 ft / 1.5 M drops to concrete.
Flexible Input Options	• Select from Standard, Long Range, and Advanced Long Range Laser, Linear Imager and 2D Imager scan engines • Select from 26-Key Standard Alphanumeric; 52-Key Full Alphanumeric and 5250 support
Industry Leading Mobile Computing	• Microsoft® Windows Mobile® and Windows® CE provide easy-to-use graphical user interfaces and a host of powerful computing technologies. • Intel XScale Microprocessor and 802.11b/g radios deliver superior mobile computing performance.
Usability & Productivity	• The 3.5" QVGA 64K Color Active Matrix Display provides superior low-light and outdoor visibility while maximizing data displayed, yielding higher productivity. • The loudest beeper available for audio feedback in noisy industrial environments.



The Falcon 4400 Series has tested compatible with Cisco's wireless solution. The Cisco Compatible logo signifies that PSC's product has undergone interoperability testing by PSC together with Cisco and a third-party test house based on testing criteria set by Cisco. PSC is solely responsible for the support and warranty of its product. Cisco makes no warranties, express or implied, with respect to PSC's product or its interoperability with the listed Cisco product(s) and disclaims any implied warranties of merchantability, fitness for a particular use or against infringement.



Copyright © PSC Inc. 2005-2006. All rights reserved. • Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from PSC. • PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. • PSC, the PSC logo, and Falcon are registered trademarks of PSC Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com • Product specifications are subject to change without notice.



PSC Inc.
959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140
www.psc.com

Falcon® 4400 Series

Windows® Based Mobile Computer



Features

- Choice of Microsoft® Windows Mobile® or Windows® CE Operating Systems
- Supports 802.11b and 802.11g Radios
- Standard/Long Range/Advanced Long Range Integrated Laser Scanner, or Linear/2D Imager Options
- Keypad options include 26-key, 48-key, 52-key, and 5250 emulation versions
- Ergonomic Design
- Rugged design survives multiple 5 ft / 15 M drops to concrete
- Tethered Stylus provides enhanced stylus security
- Intel® XScale™ PXA255 400MHz
- Bright 64K Color TFT Active Matrix QVGA display
- Industry leading beeper volume
- Instant-On Trigger (Falcon 4420 Only)

Accessories

- Powered Vehicle Dock
- Single-Slot Dock and Four-Slot Dock
- Four-Slot Battery Charger
- Handle/Handstrap Conversion Kit
- Holsters/Softcases
- USB Data Cable
- Serial Charging Cable
- Serial Printer Adapter



The Falcon 4400 Series has been tested compatible with Cisco's wireless solution. The Cisco Compatible logo signifies that PSC's product has undergone interoperability testing by PSC together with Cisco and a third-party test house based on testing criteria set by Cisco. PSC is solely responsible for the support and warranty of its product. Cisco makes no warranties, express or implied, with respect to PSC's product or its inter-operation with the listed Cisco product(s) and disclaims any implied warranties of merchantability, fitness for a particular use or against infringement.



Copyright © PSC Inc. 2004-2006. All rights reserved. • Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from PSC. • PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. • Falcon, and the PSC logo are registered trademarks of PSC Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. • Product specifications are subject to change without notice.

Mechanical

Dimensions

Length: 9.0" / 22.6 cm Width at display: 3.5" / 8.6 cm
Width at grip: 2.5" / 6.4 cm Height at grip: 1.6" / 4.1 cm

Weight: 23.3 oz / 724 g (Will vary depending upon the configuration selected. Falcon 4400 model shown with radio, scanner, and battery pack)

Display: 3.5" active matrix TFT QVGA display, 320 x 240, pixels; 64K colors

Indicators: Good read LED; scan LED

Keypads: 26-Key Standard Alphanumeric; 48-Key (handheld version only) Full Alphanumeric and 5250 support; 52-Key Full Alphanumeric and 5250 support

Construction: Industrial, polycarbonate/ABS-blend plastic shell with thermoplastic urethane overmold

Environmental

Temperature Rating

Operating: 14° to 122° F / -10° to 50° C
Storage: -13° to 158° F / -25° to 70° C

Humidity: 5 to 95% NC

Shock: Multiple 5.0' / 15 M drops to concrete

Water & Dust: IEC529, Rating IP54DW

Optical	Laser Scan Engine		Linear Imager	2D Imager
	SR*	LR*/ALR*		
Light Source	650 nm	650 nm	645 nm	626 nm
Scan Rate	35 ± 5 scans/sec.	35 ± 5 scans/sec.	36 ± 5 scans/sec.	N/A
Ambient Light Immunity				
Artificial Light	4,844 Lux	4,844 Lux	100,000 Lux	N/A
Sunlight	86,112 Lux	86,112 Lux	100,000 Lux	100,000 Lux

* Key: SR = Standard Range, LR = Long Range, ALR = Advanced Long Range.

DEPTH OF FIELD TABLE Typical Range Comparisons				
Label Density	Laser Scan Engine			2D Imager
	SR*	LR*	ALR*	
5 mil UPCA	30-50' / 8-13 cm	—	—	—
75 mil	25-90' / 6-23 cm	—	—	—
8 mil	—	—	—	2.5-6.6' / 6-17 cm
10 mil	25-150' / 6-33 cm	15-24' / 39-61 cm	—	15-70' / 4-18 cm
13 mil Code 39	—	—	150-450' / 38-114 cm	25-125' / 4-20 cm
15 mil Code 39	25-119' / 6-48 cm	9-33' / 23-84 cm	20-50' / 5-127 cm	21-128' / 5-33 cm
15 mil Data Matrix	—	—	—	23-92' / 6-23 cm
15 mil QR Code	—	—	—	31-78' / 8-20 cm
20 mil Code 39	10-29' / 3-74 cm	11-47' / 28-119 cm	—	15-115' / 4-29 cm
30 mil Code 39	—	—	32-85' / 81-216 cm	—
35 mil MaxiCode	—	—	—	21" / 5-28 cm
40 mil Code 39	25-30' / 6-76 cm	13-83' / 33-211 cm	—	30-150' / 8-38 cm
55 mil Code 39	40-45' / 10-114 cm	16-100' / 41-254 cm	26-100' / 66-254 cm	—
70 mil (reflective)	—	47-199' / 119-505 cm	113-249' / 287-632 cm	—
100 mil (reflective)	—	59-240' / 150-610 cm	124-350' / 315-889 cm	—

* Key: SR = Standard Range, LR = Long Range, ALR = Advanced Long Range.
Minimum distance determined by symbol length and scan angle. Dependent upon printing resolution, contrast, and ambient light.

System

Operating System: Windows® CE v4.2 or v5.0, Windows Mobile® v5.0

Microprocessor: Intel® XScale™ PXA255, 400 MHz

Memory

Windows® CE: RAM: 64 MB or 128 MB; Flash: 64 MB

Windows Mobile®: RAM: 64 MB; Flash: 64 MB

Dock Communications: USB 1.1 (ActiveSync) & RS-232 (ActiveSync and other RS-232 protocols)

PC Card: Internal PC Card Type I/II slot

Beep Tone: 86dBA (at 24" / 61cm) / 100dBA (at 10 cm) (typical)
Programmable for pitch and duration

Power Options

Rechargeable Lithium Ion Battery Pack (2000 mAh)

Falcon Single and Four-Slot Dock with power supply

Advanced Power Management: (without PC Card & backlight):

Sleep/off mode with programmable timeout: 5 mA; Idle mode: 60 mA (typical); Operating mode: 155 mA (typical). Rechargeable lithium backup battery; Low battery indicator (display icon)

Radio Support

Windows® CE: 802.11b or 802.11g

Windows Mobile®: 802.11g

System Support: VT100/220, HP700/92, IBM 3270/5250 terminal emulators; Browser support via Microsoft® Internet Explorer; TCP/IP Communications

Management Tools: Falcon Desktop Utility (FDU) for security & configuration; Falcon Management Utility (FMU) or Wavelink® Avalanche for remote device management & software distribution.

Development Environments:

Windows® CE: Embedded Visual C++, Visual C#.NET, Visual Basic .NET, Personal Java 1.1, Java Virtual Machine (JVM), Falcon® CE Developers Toolkit, and Wavelink® Studio.

Windows Mobile®: Visual Studio 2005 and Wavelink® Studio.

Decoding Capability (auto-discrimination)†

1D Codes

- Code 32, 39, 93
- Codabar
- Code 128
- Code 128 ext.
- EAN/JAN 8, 13
- EAN 128
- UPCA, E
- Interleaved 2/5
- Matrix 2/5
- MSI / Plessey
- Standard 2/5
- Code 39 Full ASCII
- EAN/UPC 2 digit ext.
- EAN/UPC 5 digit ext.
- EAN/UCC Composite
- RSS-14/RSS Limited

2D Codes

- PDF-417
- Micro PDF-417
- U.S. Currency Serial Number
- RSS Expanded
- Aztec Code
- MICR E 13 B
- Data Matrix
- Maxi Code
- QR Code
- OCR-A/B
- Postal Codes

† Please refer to the appropriate Product Reference Guide (PRG) for specific symbology support for the laser scan engine or imaging scan engine options.

Safety and Regulatory

Electrical: EN60950, UL60950, CSA60950

Battery: IATA/UN

Emissions: FCC Part 15C, EN55022, VCCI, ICES-003, CNS 13438, AS/NZS 3548

Radio: FCC Part 15.247, EN 300 328

Laser Classification: CDRH Class II

CAUTION: Laser Radiation—do not stare into beam; IEC 60825-1, Class 2; Class 3R for ALR devices

Restriction of Hazardous Substances: Complies to EU RoHS



PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

www.psc.com

