



D4 202

Label Printer

D4 202 is a compact size 4" desktop label printer with a industrial level equipments and high performance. D4 202 is equipped with a colorful backlight LCD with clear image display that makes the menu friendly to users. Multiple communication ports, SD slot for the data storage, real time clock for time and date printing application are some of the main features that makes this label printer ideal for all range of application. Two models available D4 202 and D4 202 ETH with Ethernet interface on board.



CUSTOM 4CARE

Service programs for you
Discover Custom4Care



Custom Designer Tool, the professional label editor, easy to use and equipped with all the features required by the market. The software, completely free, is complete with printers configuration tool and printing driver.
Discover Custom Designer Tool

TECHNICAL SHEET

	D4 202	D4 202 ETH
Printing Method	Direct thermal / Thermal transfer	
Resolution	203 dpi	
Printing speed	5 ips	
Print Width	104 mm	
Sensors	Moveable see-through and reflective sensor Ribbon sensor Cover open sensor	
RAM Memory	128 MB	
Display	Colorful 2.8" backlight LCD display, 240 × 320 dots	
Control Panel	4 multi-functional keys	
Media	Maximum label width: 110 mm Minimum label width: 15 mm Maximum roll diameter: 127 mm Core diameter: 25.4 mm Media thickness: 0.06 mm to 0.2 mm Media type: Continuous, die-cut, tag, fan-fold, black mark	
Ribbon	OD: 39 mm Max length: 100 m Width: 25.4 mm to 110 mm ID: 12.7 mm Ribbon type: Wax, wax/resin, resin	
Emulation Language	PEPL, PDPL, PZPL	
Interfaces	USB port USB master port Serial port Ethernet port 10/100Mbps (optional)	USB port USB master port Serial port Ethernet port 10/100Mbps on board
Supported 1D/2D Barcodes	Code39 stand or extended, Code39 with check digit, Code93, Code128 UCC, Code128 Auto A,B,C mode, EAN8, EAN8/13 2&5 digit add-on, EAN13, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Interleaved with human readable check digit, UCC/EAN 128, UPC-A, UPC-A 2&5 digit add-on, UPC-E, UPC-E 2&5 digit add-on, UPC Interleaved 2 of 5, Code 11 PDF417, Maxicode, Data Matrix, QR code	
Fonts	5 internal expandable bitmap fonts (alpha-numeric) 2 internal expandable bitmap fonts (numeric only) Downloadable soft font 4 directions: 0, 90, 180, 270 degrees	
Image	PEPL: PCX, Direct binary graphic	
Options	Peeler kit Cutter Ethernet module	
Power	Switching power adapter Input: 100 to 240 V, 1.8 A, 50~60 Hz Output: 24 V, 2.5 A	
Audio	Beep sound when error occurs	
Environment	Operation: 5 °C to 45°C Storage: -20 °C to 50 °C	
Humidity	Operation: 0% to 90% non condensing Storage: 5% to 95% non condensing	
Dimensions	263 mm (L) × 200 mm (W) × 188 mm (H)	

D4 202

D4 202 ETH

Weight

2 kg

MODELS



911MK020100333

LABEL PRINTER D4 202 USB
RS232 WITH DISPLAY BLACK



911MK020100733

LABEL PRINTER D4 202 ETH USB
RS232 WITH DISPLAY BLACK

CUSTOM S.P.A. - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: TI80WI0

The technical data on this website are not binding and may be changed without advanced notice.
Last update: 22 April 2021