



1D & 2D



Android 8.1



Bluetooth 4.1



Megapixel



Laser aimer



6" screen



Touchscreen



USB-C



6000 mAh



Micro SD



Camera



1.2M drop



IP65



4G



WIFI Dual Band



NFC



GPRS



Location



Warranty 2 Years



**SD60
Pegasus**
Speedata

Features

Supports

1D and 2D barcodes.

Software.

Built on Android 8.1.

Display.

6.0 inch (2160 x 1080) 5 point capacitive touch screen.

Processor.

Octa core 2.0GHz CPU.

Offers.

Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz). Bluetooth 4.1, camera, GPS, NFC, GSM, WCDMA.

Accessories.

Supplied with cradle.



Suggested industries



Industrial



Logistics



Retail



Transportation



Warehousing

SD60 Pegasus Technical specifications

Data Capture	
Barcode scanning	All major symbologies, including AZTEC, CODABAR, CODE11, CODE128, EAN128, CODE39, CODE49, CODE93, COMPOSITE, DATAMATRIX, EAN8, EAN13, INT25, MAXICODE, MICROPDF, PDF417, POSTNET, OCR, QR, RSS, UPCA, UPCE, ISBT, BPO, CANPOST, AUSPOST, IATA25, CODABLOCK, JAPOST, PLANET, DUTCHPOST, MSI, TLC39, TRIOPTIC, CODE32, STRT25.
Performance	
Operating System	Android 8.1
Processor	Octa-core 2.0GHz
Memory RAM	4GB
Memory Flash	64GB
Physical	
Audio	Front dual stereo speakers, volume 90db ± 3db (test distance 10cm)
Battery Type	6000mAh
Camera	Rear 13MP AF, high light LED flash, front 5MP camera
Dimensions (mm)	160mm x 80mm x 15.8mm
Display	6.0" (2160x1080) IPS highlight screen
Expansion Slot	2 Nano SIM card slots, 1 Micro SD card slot
Expected Charge Time	PE fast charge, full charge time < 4h
Interfaces	USB Type-C
Keypad	2 volume buttons, 2 function buttons (1 left, 1 right), 1 power button
Notifications	Sound, vibration, LED
Sensors	Gsensor, Ambient light sensor, Proximity sensor, COMPASS
Touch Panel	5-point capacitive touch screen
Weight	300g (with battery)
Wireless	
WWAN RADIO	FDD-LTE B1/B3/B5/B7/B8, TDD-LTE B38/B39/B40/B41, TDSCDMA B34/B39, WCDMA B1/B2/B5/B8, GSM B2/B3/B5/B8, CDMA1x/CDMA2000 BC0/BC1
WLAN RADIO	IEEE 802.11 a/b/g/n 2.4G 5G dual frequency
WPAN RADIO	Bluetooth 4.1 BLE

Newland AIDC EMEA

Email address: info@newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2025, all rights reserved



SD60 Pegasus Technical specifications

RFID	ISO14443A/B, 15015693, NFC Reading distance: 0~5cm
GPS	GPS+ BD+GLONASS
Environmental	
Operating Temperature	-20°C to 55°C
Storage Temperature	-30°C to 70°C
Humidity	5%-95% (non-condensing)
Electro Static Discharge (ESD)	±15kV air discharge, ±8kV contact discharge
Drop	1.2 meters drop to concrete floor
IP Rating	IP65
Certifications	
Hardware	CCC, CTA, CE
Warranty	
Standard	2 years