



Simple design

The CMP-30II printers are designed like all Citizen printers to be simple to use and easy to operate.

Intuitive operation

This, combined with the durable, strong plastic case which is designed to take the occasional knock, means our printers keep running and running.

High capacity media rolls

The CMP printers can accept media rolls with a diameter of approximately two inches. In addition, the CMP-30IIL model supports label printing as well as receipts via the integral label gap sensor.

Applications

- Hospitality
- Law Enforcement
- Logistic / Transport
- Retail
- Ticketing
- Warehousing



Portable printers for all your receipt and labelling needs

Specifications

Model	CMP-30II
Resolution	203 dpi
Print Speed (maximum)	4 inches per second (100 mm/s)
Print Width (maximum)	72 mm
Media Width (min to max)	25 - 80 mm
Roll Size (max), Core Size	Diameter 2.20 inches (56 mm)
Media Sensor	Paper end and reflective black mark
Main Interface	Dual Interface Serial (RS-232 /mini DIN connector), USB (mini B connector)
Optional interfaces	Bluetooth with Apple™ MFi compatibility, Bluetooth Class 2 , Compact Wireless LAN, Bluetooth 4.2
Environmental rating, drop test	Exceeds IP42. Survives multiple drops of 1.5 metres
Battery type and capacity	Hard pack 7.4V 2600mAh
Emulations (Languages)	CPCL™ compatibility, ESC/POS™ , Zebra® ZPL2®
Size (W x D x H) and Weight	120 x 152 x 70 mm, 0.6 Kg

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CMP-30II

Mobile

Features & Benefits

- Paper load: Quick and easy media changing - drop-in paper loading
- Printing Speed: High speed printing - up to 100 mm per second
- Mobile-POS ready
- Powerful - High capacity batteries for a full day's operation (status indicated by LED)
- Mains charger included
- Standard clip-in battery
- Car adapter option
- Additional batteries
- External battery charger
- Soft cases and shoulder straps
- USB and Serial cables
- Magnetic Strip Reader: Factory option. ISO 7811/2, JIS standards. Dual track (1+2+3), 10-15 cm/s swipe speed
- Smart Card Reader (IC Card): Factory Option. 9,600 bps read speed, internal 1-channel
- Car adapter