

COLORFUL



SMALL, BRIGHT, LIGHTWEIGHT AND EASY TO CONNECT

Increase productivity and reduce data errors in mobile business Applications with the Socket Bluetooth Cordless Hand Scanner (CHS), a wireless barcode reader for smartphones and tablets that's small, portable and provides fast, industrial-class scanning performance.

CHS 7Ci - General Purpose Scanner

#1 Choice for Tablet-Based Retail Point of Sale
Smallest, lightest and most affordable CHS model, available in bright colors to enhance corporate branding in retail or customer service enable personalization, and make scanner easy to find.

CHS 7Mi - Laser Scanners

For Special Lighting Conditions or Barcode Requirements
Featuring a Class 2 laser, the CHS 7Mi works well in bright sunlight, in low light, as well as with barcodes that are small, tightly spaced, on shiny surfaces or behind plastic or glass.

CHS 7Qi - For 2D and 1D Barcodes

For high performance 2D and 1D barcodes printed or on-screen.
Reads barcodes displayed on screen of smartphone, laptop, tablet, etc.

Software Development Kit (SDK)

- SocketScan 10 SDK available to members of Socket Mobile Developer Program (\$19.95 (€19.95)/year)

Hardware Features

- Easily connect to Bluetooth enabled smartphones, tablets, PDAs, notebooks and desktop computers:
 - Apple® iOS
 - Android® OS
 - Windows® 8, 7, Vista, XP
 - Windows Embedded Handheld (Windows Mobile)
 - Mac OS
- Made with antimicrobial plastics to provide an extra layer of protection to the device against the spread of potentially harmful microbes
- Battery Friendly technology enables up to 14-hours battery life on a single charge
- Scanner automatically connects to the last device or computer it paired and connected to
- Wear around neck or attach to belt with included lanyard / belt clip for convenient access to scanner
- LED and beeps indicates good scans, ideal for noisy environments where beeps are hard to hear or Applications where beeps must be disabled
- Supports both Bluetooth HID and SPP connections for easy setup with no software installation or advanced scanner control and SDK support²

Special Features for Apple iOS

- Certified by Apple for iPad, iPad mini, iPhone, and iPod touch
- Quickly access Apple iOS on-screen keyboard by pressing a scanner button
- Authentication chip enables two-way communications with Apple devices running a compatible App developed with SocketScan 10 SDK. View Apps at: <http://www.socketmobile.com/appstore>
- App to modify beep, LED, vibrate and other settings

Software - Android, Windows

- SocketScan 10 keyboard wedge enters scanned data into any App, no custom programming needed
- Socket EZ Pair automates Bluetooth setup - just scan the barcode on the screen to connect¹
- Suffix support -- automatically add a carriage return or tab after each scan of data
- Data editing -- reformat, extract or manipulate data
- Scanner configuration -- modify beep, LED, vibrate, and symbology settings. View Scanner's battery level

¹On-screen barcode not compatible with laser scanners. Requires installation of SocketScan 10 software for Android/BlackBerry/Windows or iOS App developed with SDK.

²Some smartphones/devices do not support both HID and SPP

CHS Model	7Ci	7Mi	7Qi
Scanner SKU #	Blue: CX2887-1486 Gray: CX2870-1409 Green: CX3351-1662 Red: CX2885-1484 White: CX2895-1508 Yellow: CX2883-1480	Blue: CX3304-1514 Gray: CX2872-1411 Green: CX3352-1663 Red: CX3302-1512 White: CX3306-1516 Yellow: CX3300-1510	Blue: CX3314-1534 Gray: CX3308-1528 Green: CX3353-1664 Red: CX3312-1532 White: CX3316-1536 Yellow: CX3310-1530
Dimensions	5.07 x 1.57 x 1.36 in. (129 x 40.1 x 34.6 mm)	5.07 x 1.57 x 1.36 in. (129 x 40.1 x 34.6 mm)	5.07 x 1.57 x 1.36 in. (129 x 40.1 x 34.6 mm)
Total Weight	1.6 oz (45 g)	1.8 oz (51 g)	1.6 oz (45 g)
Drop Specification	Multiple 3.3 ft (1m) drops to vinyl covered concrete		
Temperature, ¹ Relative Humidity	Operating Temperature: +32 to +122°F (0 to + 50°C) Storage Temperature: -22 to + 158°F (-30 to + 70°C) Relative Humidity: 5% to 95% non-condensing		
Ambient Light	Sunlight: 0 - 110,000 lux	Sunlight: 100,000 lux Artificial light: 4,844 lux	Sunlight: 0 - 110,000 lux
Battery Type	Two AAA NiMH rechargeable batteries		One Lithium ion rechargeable battery
Battery Life	~14 hours or 15,000 scans per charge		~10 hours or 5,000 scans per charge
Scanner type	Imager (1D)	Class 2 laser (1D)	Omni-directional Imager (2D)
Scan Barcodes on Device Screens	✓		✓
Scans VIN through Windshield		✓	
Vibrate Mode for Good Scans	✓	✓	✓
Symbologies Decoded	Bookland EAN (ISBN / EAN-13), Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN, UPC/EAN/JAN supplemental redundancy, Coupon Report, ISSN EAN, Inverse 1D, ISBT concatenations, Matrix 2 of 5	Bookland EAN (ISBN / EAN-13), Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN	1D: Bookland EAN (ISBN / EAN-13), Codabar (including ISBT 128 bit concatenation), Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN 2D: Aztec, Codablock, Data Matrix, GS1 (EAN.UCC), Matrix 2 of 5, Maxicode, PDF 417, Macro PDF 417, Micro PDF 417, QR Code, Standard 2 of 5, Telepen, TLCode 39 Postal: Australia Post, BPO 4, Canada Post, Dutch Post (KIX), Japan Post, Planet, Postnet, RM4SCC, Sweden Post, TLCode 39, 4 State Code, USPS Intelligent Mail
Scan Repetition Rate	5 scans/sec	5 scans/sec bi-directional	Omni-Directional / Auto-Adaptive 5 images/sec
Optical Resolution	5 mil minimum	0.004 in. (0.102mm) min./barcode element width	752(H) x 480(V) pixels, 256 gray levels
Print Contrast	Minimum 20%	Minimum 25% MRD at 650 nm	Down to 25%
Scan Angle	53.3° ± 3°	Wide (default): 47° ± 3° Narrow: 35° ± 3°	Horizontal: 38.9° Vertical: 25.4°
Decode Distance ³	5.7 to 50.8 cm (2.25 to 20 in.)	3.8 to 114+ cm (1.5 to 45+ in.)	4.8 to 40.6 cm (1.9 to 16 in.) Depends on symbol size, symbology, label media, W-N ratio, scan angle.
Bluetooth Profile Support	Human Interface Device (HID) and Serial Port Profile (SPP) Some OS versions or smartphone/tablet models support only one profile.		
Bluetooth Version	Bluetooth 2.1 + EDR (Enhanced Data Rates) with 56 bit data encryption		
Radio Range	Up to 10 m (33 ft), depending on environment, range limit is usually due to the Master Device (Phone, Tablet, or Notebook)		
OS Support			
Apple iOS	✓	✓	✓
Android OS	✓	✓	✓
Windows 8, 7, Vista, XP	✓	✓	✓
Windows Embedded Handheld, Mobile	✓	✓	✓
Mac OS (HID only)	✓	✓	✓
SocketScan™ 10 Software	Keyboard wedge software featuring Socket EZ Pair for Android, BlackBerry, Windows. Scanner Settings configuration utility also included.		
SocketScan 10 SDK	For Apple iOS, Android, BlackBerry, Windows. Available to members of Socket Mobile Developer Program (\$19.95/year) http://developer.socketmobile.com		
Included Items	CHS barcode scanner, AAA NMH rechargeable batteries (2), USB AC charger kit, lanyard/belt clip with retractable tether, software		
Warranty	Scanner: One year Accessories: 90 days		
SocketCare Extended Warranty	Sold separately. SocketCare Plus 2 Year - SKU# SC1804-1349 SocketCare Plus 3 Year - SKU# SC1805-1350 http://www.socketcare.com/		
Charging Cradle	SKU# AC4054-1381		
DC Power Supply (Car Charger)	SKU# AC4057-1384		
Battery Replacement Kit:	Two AAA NiMH Rechargeable Batteries		SKU# AC4059-1479
Electrical Safety	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2		
Environmental	RoHS		
EMI / RFI	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELECOM		
Laser / LED Safety	IEC 60825-1, EN 60825-1		

¹Temperature ranges may vary with battery shelf life. ²Battery life may vary with vibrate settings and work environment. ³Depends on symbol size, symbology, label media, W-N ratio, scan angle.

sales@socketmobile.com		Toll-Free	+1 800 552 3300 (USA/Canada)	Asia Pacific	+1 510 933 3122
Worldwide	+1 510 933 3000	EMEA / UK	+44 7787 112109	Latin America	+1 510 933 3153



800 729 0236
www.logiscenter.us



0241 9550 9225
www.logiscenter.de



01 82 88 44 70
www.logiscenter.fr



020 3318 8265
www.logiscenter.co.uk



0720 115814
www.logiscenter.at



02 58 80 583
www.logiscenter.be



911 433 048
www.logiscenter.com



02 4792 1697
www.logiscenter.it



308 800 842
www.logiscenter.pt

About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 60,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.



All Brands Technical Service


Our Brands




Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)