

ProLite E1780SD-B1

Reliable home and office solution

The 17" ProLite E1780SD is a LED-backlit monitor with good response time, high contrast and sRGB and gamma correction functions that permit even the finest nuances of colour to be set accurately. The ProLite E1780SD includes DVI and VGA connectivity and is available in black.

DISPLAY CHARACTERISTICS

Diagonal	17"
Panel	TN LED
Display area h x w	270.3 x 337.9 mm; 10.6" x 13.3"
Response time	5 ms
Contrast	1000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	250 cd/m² typical
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.264 x 0.264 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	5 : 4

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	14 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

DIMENSIONS & WEIGHT

Dimensions w x h x d	370 x 379.5 x 178 mm
Weight	2.6 kg

INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D
HDCP	yes
	D-Sub, DVI-D

SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, NL, PL, RU, JP, Chinese simplified and traditional) and 5 front controls (Power, Select / Input Button, Scroll Up / Audio Adjust Button, Scroll Down / i-Style Colour Button, Menu Button)
User controls	auto adjust, picture adjust (contrast, brightness, ACR, ECO), input select, audio (volume, mute), colour adjust, information, manual image adjust (H./V. position, clock, phase, sharpness), setup menu (language select, OSD position, OSD time out, OSD background, opening logo, LED), recall
Speakers	2 x 1 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Safety	CE, TÜV-Bauart, VCCI-B, GOST-R, TCO 6
Tilt angle	20° up; ° down
VESA mounting	100 x 100 mm

ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7 / 8
Included accessories	power cable, VGA (D-Sub) cable, DVI-D cable, audio cable, stand, quick start guide, safety guide

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.