



THE AFFORDABLE LITE-RAY POS WORKSTATION WITH ENERGY STAR QUALIFICATION.

Lite-ray is the durable, reliable POS workstation designed to withstand spills, static, dirt, shock and more. Its outstanding feature set and available options make it a smart choice for a wide variety of POS applications. With its open platform, Lite-ray runs virtually any software, and its Intel® Atom™ Processor is purpose-built and power-optimized to deliver more robust performance per watt. ENERGY STAR® qualification makes it ideal for better ROI. Building reliable, easy-to-run POS systems is how we're engineering a better world.

LITE-RAY WORKSTATION ADVANTAGES

- Storage options include either one or two 2.5" HDD or Solid State Disks (SSD), or a combination of both
- Dual backlight, high resolution/high contrast 15" antiglare LCD for easier order taking
- Second LCD port for 15" rear display option enables promotional selling and order confirmation
- Optional integrated magnetic card reader is mountable in two different positions to save counter space
- Optional second HDD with RAID 0,1 support provides data protection and backup
- Optional security features include fingerprint reader/biometric for operator ID verification



1.877.726.2767
panasonic.com/lite-ray

SOLUTIONS FOR FOOD SERVICES

COMMON SPECIFICATIONS

Environmental condition

■ Operating Temperature	+5°C – +40°C
■ Operating Humidity	15% RH – 85% RH (no dew)
■ Storage Temperature	-30°C – +60°C
■ Storage Humidity	10%RH – 90%RH

POS WORKSTATION

JS-925WS

■ CPU	Type	Intel® Atom N270
	Package	µFCBGA8
	Frequency	1.6GHz
■ Main Memory	Capacity	Standard: 1GB (use 1 SO-DIMM slot) Maximum: 2GB
	Slot	1 x DDR2 SO-DIMM slots, 200pin
■ BIOS	Type	DDR2-400/533/667
	Type	Flash ROM
	BIOS function	ACPI 1.0b, APM 1.2, PXE boot, USB-FDD boot, USB-CD ROM/DVD ROM boot, USB Flash Memory boot
■ Supported OS		Windows XP SP3, WEPOS 1.1 SP3, POSReady 2009, Windows Vista Ultimate, Linux Kernel 2.6, Windows Embedded 7, POSReady 7
■ HDD	Type	2.5"
	Size	160GB minimum
	I/F	SATA (2.5" type)
Other Disk Drive (Option)		External USB FDD interface is supported External USB DVD/CD-ROM interface is supported
■ Local Area Network		Ethernet (10BASE-T/100BASE-TX) Note : Wake On LAN supported
■ Display	Type	TFT type LCD with dual backlight
	Display size/pixel	15": 1024 x 768 (XGA)
	Colors	260,000 colors or more
	Brightness	15": 250 nits (without touch panel)
■ Touch panel	Type	5-wire resistive
	Interface	Serial
	Life	30 million touches or more
	Surface	Non-glare surface treatment
■ I/O ports	Serial	4 Ports 9pin D-SUB male - Note: 2 ports are powered
	Video	1 Port 15pin D-SUB female - Note: The Dual Display function is supported
	LAN	11 Port RJ-45
	USB 2.0	2 USB ports: IO panel, 1 USB port: touch screen unit, 1 USB port: rear, 2 USB ports: IO panel (Option: JS-925CB)
	Audio	1 port Line-out (Option: JS-925CB)
	Cash drawer	RJ type drawer located on I/O panel
■ Expansion I/F		For communication board: JS-925CB -IO extension + Speaker
■ Switch		1 power switch (power on/off) - Shutdown activated by momentarily pushing the on/off button
■ LED		1 power (2 colors: green, red) green ON: power ON red ON: power OFF 1 HDD (green)
		Light ON: HDD accessing 1 LAN (green) Light ON: Send/Receive
■ Power supply input		AC100V-240V, 50/60 Hz, 1.6A
■ Size		15": Approx. W364mm x D291mm x H413mm, Carton box: Approx. W514mm x D358mm x H548mm
■ Mass		Net weight: Approx. 7.57 kg, Gross weight: Approx. 9.18 kg
■ Backup battery I/F		Optional, note: retention time: 2 minutes

OPTIONS

■ Communication board	JS-925CB-010 expansion IO I/F + speaker, I/F : expansion I/F - Line-OUT 1port - USB 2.0 2ports - Din type drawer 1port (Same as JS-950WS) Note: The power of +12V, 1A is required to drive DIN type cash drawer
■ Backup battery (Spare parts)	Ni-CD: N4HKLNB00007, Ni-MH: BT50024A, backup battery for AC power fail, Note: retention time: 2 minutes, battery charge function
■ Magnetic card reader	JS-950MG-010, Magnetic strip reader module, I/F : USB (internal connector for MSR) Virtual COM
■ USB HUB board	JS-925HU-010, USB-HUB board, use for 2 USB ports of Display unit

1.877.726.2767
panasonic.com/lite-ray

Lite-ray





800 729 0236
www.logiscenter.us



0241 9550 9225
www.logiscenter.de



01 82 88 44 70
www.logiscenter.fr



020 3318 8265
www.logiscenter.co.uk



0720 115814
www.logiscenter.at



02 58 80 583
www.logiscenter.be



911 433 048
www.logiscenter.com



02 4792 1697
www.logiscenter.it



308 800 842
www.logiscenter.pt

About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 60,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.



All Brands Technical Service


Our Brands




Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)