

# CITIZEN

## Fast, tough and easy to use receipt printer

Protected by Spill-Shield™



### One touch top cover

Spill-Shield™ design to prevent damage from moisture or foreign objects to the internal mechanism. This makes it the best protected printer at the POS. No matter where you are: bar, restaurant or shop nothing can stop your printer to do it's job.

### Internal power supply

All 80mm POS printers from Citizen offer an internal power supply.

## CT-S2000

Other

### Applications

- Hospitality
- Journal
- Kiosk
- Kitchen
- Retail



Confidence in point-of-sale

TOMORROW'S PRINTING TODAY



USB is default in addition to serial or parallel interface boards. This makes the CT-S2000 a future-proof investment.

## Specifications

| Model                       | CT-S2000                                                                   |
|-----------------------------|----------------------------------------------------------------------------|
| Printing Technology         | Direct Thermal                                                             |
| Resolution                  | 203 dpi                                                                    |
| Print Speed (maximum)       | 220 mm /sec.                                                               |
| Print Width (maximum)       | 80 mm                                                                      |
| Media Width (min to max)    | 58 / 60 / 80 / 82.5 mm                                                     |
| Roll Size (max), Core Size  | 102 mm outside diameter                                                    |
| Main Interface              | Dual Interface Serial (RS-232C), USB (version 2.0, full speed)             |
| Optional interfaces         | Ethernet (SEH), Serial (RS-232C compliant), Parallel (IEEE 1284 compliant) |
| Power supply                | 100 - 240V, 50/60hz                                                        |
| Reliability                 | 200 Million pulses or 150 Km, 2 million cuts                               |
| Emulations (Languages)      | ESC/POS™                                                                   |
| Drivers and software        | Free-of-charge from website, including support for various platforms       |
| Flash (Non-Volatile Memory) | 384K bytes                                                                 |
| Size (W x D x H) and Weight | 147x207x147 mm, 1.2 Kg (AC type) / 1.8 Kgs (DC type)                       |
| Cutter                      | Guillotine type, full and partial                                          |
| EMC and safety standards    | CE, TUV, UL, C-UL, FCC class A                                             |

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

## CT-S2000

### Other

## Features & Benefits

- Paper exit: Front exit, top loading
- Printing Speed: Fast print out of receipts - up to 220mm per seconds
- Low space requirement - integrated power supply enables clean work station
- Easy notification - built-in buzzer



The fully loaded high end thermal printer with built in protection