



MB2i

ULTIMATE PERFORMANCE
AND MOBILITY

FEATURES

- Fast Speed Printing
- Durability
- Enduring
- Anti-microbial Casing
- 2-Colour Printing

APPLICATIONS

- Logistics
- Warehouse
- Retail
- Mobile Printing
- Field Service

TECHNICAL INFORMATION

MB200i / MB201i

PRINTING SPECIFICATION		MB200i	MB201i
Printing Method		Direct Thermal	
Print Resolution, dots/mm (dpi)		8 dots/mm (203dpi)	
Max. Print Area	Width, mm (inch)	48mm (1.89")	
	Length, mm (inch)	160mm (6.3")	
Print Speed, mm/sec (ips)		Up to 103mm/sec (4ips)	
CPU		32 bit RISC	

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)				
Sensor Type			I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)	
Media Type			Roll die cut labels, Plain paper face stock, Linerless labels, Synthetics and Continuous stock	
Media Thickness			0.08 – 0.18mm (0.003" – 0.007")	
Label Shape	Diameter		Max. outside diameter: Ø 67mm (2.64"), Core diameter: Ø 19mm (0.75") or Ø 25.4mm (1")	Max. external diameter: Ø 58mm (2.28"), Core diameter: Ø 19mm (0.75") or Ø 25.4mm (1")
	Wind Direction		Face-out	
Label Size	Continuous	Width	25.4 – 55mm (1" – 2.17")	
		Length	13 – 160mm (0.51" – 6.30")	
	Tear-Off	Width	25.4 – 55mm (1" – 2.17")	
		Length	13 – 160mm (0.51" – 6.30")	
	Dispenser	Width	25.4 – 55mm (1" – 2.17")	
		Length	13 – 160mm (0.51" – 6.30")	

FONTS / SYMBOLOGIES			
Fonts	Standard Fonts	Bitmap Fonts Alphanumeric and Symbol: XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)	
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC	
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)	
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°	

INTERFACE CHARACTERISTICS			
Interface	Standard Model	RS-232C, Infrared (IrDA Ver.1.2, BHT protocol, IrCOMM, IrOBEX)	
	Bluetooth Model	Bluetooth, RS-232C, Infrared (IrDA Ver.1.2, BHT Protocol, IrCOMM, IrOBEX)	
	Wireless LAN Model	Wireless LAN 802.11b/g, RS-232C, Infrared (IrDA Ver.1.2, Standard Protocol, BHT Protocol, IrCOMM, IrOBEX)	

OPERATING CHARACTERISTICS			
Power Requirements		Input voltage AC100-240V (auto switching)/40W Input voltage printer: 9V/4,4A	
Dimensions w/rubber boot		(W x D x H): 88 x 128 x 73mm (3.46" x 5.04" x 2.87")	(W x D x H): 88 x 119 x 64mm (3.46" x 4.69" x 2.52")
		Industrial version: 158 x 116 x 94mm (6.22" x 4.57" x 3.70")	
Weight		Approx. 405g (0.89 lbs) with battery installed Industrial version: 515g (1.14 lbs)	Approx. 390g (0.86 lbs) with battery installed
Environment	Operating	-15 – 50°C / 20 – 80% RH (without condensation)	
	Storage	-25 – 60°C / 20 – 80% RH (without condensation)	

MISCELLANEOUS		
Certifications		FCC, UL, CSA, CCC, CE, ROHS compliant, Bluetooth® certified
Function	Useful Features	Auto Power Save. Printer goes to sleep mode when idle for 5 seconds. Printer will power off automatically when idle for another 5 minutes. (Programmable auto power off interval)
	Self Diagnosis Checking	Head check, Battery check, Paper end detection, Head open, Test print. MB200i has additional overcharge / over discharge protection.

OPTIONS	
Accessories	AC Adaptor, RS232 Cable, Battery Charger (single or up to 5 batteries), Battery Pack, Water Protective Case, Shoulder Strap, Belt Bag, Belt Clip (Standard), Linerless (Standard) DC/DC Converter, SATO Label Gallery™



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.


Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health




Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service