

nordicidmedea

Take a step forward and enter a new era of identification with the Nordic ID Medea. This mobile computer in contemporary design combines a large-size touchscreen display with unique functionalities and first-class performance, taking efficiency and user experience to the next level.

The Nordic ID Medea is an excellent tool for tasks that require high performance. Pair the Nordic ID Medea with Nordic ID NIDA software for a modern out-of-the-box solution. The brilliant 4.3" touchscreen offers an intuitive-to-use user interface, which is easy-to-learn and familiar to today's users. The Nordic ID Medea is equipped with our advanced high-performance RFID reader engine that delivers fast read rates and high data throughput. The Nordic ID Medea operates a full working day with only one charge.

The Nordic ID Medea is seamlessly compatible with the entire Nordic ID product portfolio. The Nordic ID Medea -series consists of the Nordic ID Medea UHF RFID Cross Dipole, Nordic ID Medea UHF RFID and Nordic ID Medea Barcode.



PRODUCT VERSIONS

NORDIC ID MEDEA
UHF RFID CROSS DIPOLE



NORDIC ID MEDEA
UHF RFID
(Q4 / 2014)



NORDIC ID MEDEA
BARCODE



**LASER
or
2D
IMAGER**

3G
UMTS / HSDPA
900/2100 MHz

GPS
Assisted GPS

WLAN
802.11 a/b/g/n
WPA2

BLUETOOTH
2.0
+ EDR Class 2

WINDOWS
Embedded
Compact 7

RFID IDENTIFICATION

NORDIC ID MEDEA
UHF RFID Cross Dipole

Supported standard: ISO 18000-6C (EPC Class 1 Gen 2)
Frequency ETSI 865.6 - 867.6 MHz or FCC/IC 902 - 928 MHz
RF Power: ERP +28 dBm (630mW)
Nominal reading distance: 4 m
Typical reading speed: 200 tags per second
Software controlled antenna polarization; Horizontal, vertical or cross-polarized

NORDIC ID MEDEA
UHF RFID
(Q4 / 2014)

Supported standard: ISO 18000-6C (EPC Class 1 Gen 2)
Frequency ETSI 865.6 - 867.6 MHz or FCC/IC 902 - 928 MHz
RF Power: ERP +20 dBm (100mW)
Nominal reading distance: 1 m
Typical reading speed: 200 tags per second

LASER IDENTIFICATION

1D laser scanner

All major 1D bar codes
Adaptive Auto-Range Laser (standard-, long- and auto-range)
Normal, hold to aim and hold down modes
Enhanced aiming mode (automatic switching between scan line / aiming dot)
Configurable scan alert sounds

2D imager

All major 1D and 2D codes
High visibility LED aimer
2 character pre and post fixes, padding, replacement
Video preview
Configurable scan alert sounds

PRODUCT HIGHLIGHTS

- Unique combination of functionality and performance
- Large 4.3" touchscreen
- Robust Gorilla Glass 2 display
- Daylight readable display
- Lightweight device
- Intuitive user experience
- Dual function foldable RFID antenna
- Software backwards compatible
- 2 years warranty

ACCESSORIES

- Desktop charging cradle with USB connection including power supply (EU, UK, US)

PREINSTALLED APPLICATIONS

MICROSOFT APPLICATIONS:

- Internet Explorer web browser
- Wordpad

PLATFORM		
CPU	ARM Cortex-A8 1 GHz	
Operating system	Microsoft® Windows® Embedded Compact 7	
Memory	512 MB LPDDR2 RAM 4 GB Flash	
USER INTERFACE		
Display	4,3" WVGA capacitive touch screen, 800 x 480 pixels, 262k colors Adjustable LED backlight, Daylight readable (Blanview), Gorilla glass 2	
Keypad	7 distinguished buttons: 3 x scan, ok, del, menu, power Individual control for each key	
Signals and indicators	Speaker for audible signals and Haptic vibra	
COMMUNICATION		
Wireless WAN (Q4 / 2014)	3G UMTS / HSDPA (900/2100 MHz) GPRS / EDGE (900/1800 MHz) (optional)	
GPS (Q4 / 2014)	Assisted GPS (optional)	
Wireless LAN	IEEE 802.11 a/b/g/n	
WLAN security	Standards: WEP, WPA, WPA2 (802.11i) Encryption: WEP, TKIP, AES	
Wireless PAN	Bluetooth 2.0 + EDR, Class 2	
LAN	Ethernet 10/100 via charger (optional)	
PAN	USB via device and charger	
POWER		
Battery	Rechargeable, removable Lithium-Ion battery pack 3500 mAh, 3.7V Up to 10 h in intensive use (standard battery)	
Charging	Desktop charging cradle with USB connection Desktop charging cradle with spare battery charging slot Typical charging time: 3 h (0 to 90 %) and 4 h (0 to 100 %)	
External power supply	AC adapter for desktop charger: input 100-240 VAC, 1A, 50-60 Hz / output 5,2 VDC, 3A, 15 W / Power adapter for EU, UK or US	
Backup battery / batteries	Back-up battery for real-time clock: keeps time for 200 days	
SIZE AND WEIGHT		
Dimensions	Nordic ID Medea UHF RFID Cross Dipole (H) 158 x (W) 83/100 x (D) 21/45 mm Nordic Medea UHF RFID & Barcode (H) 158 x (W) 83 x & (D) 21 mm	
Weight	Nordic ID Medea UHF RFID Cross Dipole ~ 420 g Nordic Medea UHF RFID & Barcode ~ 320 g	
DROP AND SHOCK		
Drop and impact resistance	1.5 m	
ESD	Contacts	+/- 4kVdc
	Air discharge	+/- 8kVdc
ENVIRONMENT		
Temperature	Operating	-20° to +55° C
	Storage	-20° to +60° C
	Charging	0° to +45° C
Relative humidity	10% to 95% non-condensing	

NORDIC ID APPLICATIONS:

- Registry backup
- IP config
- NID Menu

CONTROL PANEL APPLET:

- NID Autostart: automatic start of application after network connection is established
- NID Backlight: backlight brightness
- NID Indicators: battery level and signal level indicators
- NID Keypad: keyboard mapping
- NID LinkWatchdog: connection monitoring
- NID Menu: application manager
- NID Powerbutton: power button mapping
- NID Scanner: barcode type settings
- NID SNTP Service: network time synchronisation
- NID Touch screen: disable/enable
- NID WWAN settings

OPTIONAL APPLICATIONS

- Naurtech CETerm: terminal emulation client
- Naurtech SAP browser

SOFTWARE DEVELOPMENT ENVIRONMENT

- For all developers:
- Nordic ID MHL hardware abstraction layer
 - Nordic ID UHF RFID API
 - Nordic ID Sample applications and source code
 - Nordic ID Customizer

FOR .NET (C#, VB ETC)

- Microsoft Visual Studio 2008
- .NET Compact Framework 2.0 and 3.5
- Nordic ID SDK
- MHL API wrapper for .NET
- OpenNETCF – Smart Device Framework

FOR C++

- Nordic ID SDK
- NUR API
- MHL API

FOR HTML

- Nordic ID Sample applications

ENVIRONMENT

- Free support during and after 2 year warranty time
- Maintenance service and extended maintenance contract
- Software customization and development support
- Technology, product and integration training
- Technology and project consultation
- Project management services

All information is subject to change without prior notice.



NORDIC ID HEADQUARTERS

Myllyojankatu 2 A
FI-24100 Salo
FINLAND
tel. +358 2 727 7700
fax +358 2 727 7720
info@nordicid.com
www.nordicid.com

GERMANY

Nordic ID GmbH
Bielefeld, Germany
tel. +49 521/557717-0
fax +49 521/557717-10
info@nordicid.de
www.nordicid.de

BENELUX

Alphen aan den Rijn
The Netherlands
tel. +31 172 233 097
fax +31 172 475 653
info@nordicid.nl
www.nordicid.nl



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service