

NLB1000

Barcode laser scanner

RS232

Keyboard Wedge

USB (VCP)

+ Related products

RLB1000

- Stationary device
- Barcode raster laser scanner
- RS232, USB (VCP)
- IP 54, Metal diecast

NFT7175

- Stationary device
- Barcode CCD scanner
- RS232
- Sheet metal, 700 scans/sec

OPM5145

- Stationary device
- Omnidirectional laser scanner
- RS232, Keyboard Wedge, USB (HID/VCP)
- Zinc diecast



Operating indicators

- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

Communication

- RS232: DB9 PTF connector with external power supply
- USB: Ver. 1.1, VCP, USB-A connector

Power

- Voltage requirement: 5V $\pm$ 10%
- Current consumption: Max. 500mA

Barcode scanner Optics

- Light source: 650 nm visible laser diode
- Scan method: Polygon mirror
- Scan rate: 1000 scans/sec
- Trigger mode: Manual, multiple read, serial software trigger
- Reading pitch angle: -30 to 0°, 0 to +30°
- Reading skew angle: -60 to -7°, +9 to +60°
- Reading tilt angle: -25 to 0°, 0 to +25°
- Curvature: R>20 mm (EAN8), R>25 mm (EAN13)
- Min. resolution at PCS 0.9: 0.15 mm / 6 mil
- Depth of field: At PCS 0.9, Code 39
70 - 330 mm / 2.76 - 12.99 in (1.0 mm / 39 mil),
60 - 270 mm / 2.36 - 10.36 in (0.5 mm / 20 mil),
60 - 200 mm / 2.36 - 7.87 in (0.25 mm / 10 mil),
70 - 140 mm / 2.76 - 5.51 in (0.15 mm / 6 mil)

Supported Symbolologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, GS1 DataBar (RSS), Code 128, GS1-128 (EAN-128), IATA, Industrial 2of5, Interleaved 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post
- 2D code: MicroPDF417, PDF417

Durability

- Temperature in operation: 0 to 45 °C / 32 to 113 °F
- Temperature in storage: -20 to 65 °C / -4 to 149 °F
- Humidity in operation: 5 - 90% (non-condensing)
- Humidity in storage: 5 - 90% (non-condensing)
- Ambient light immunity: Fluorescent 4,000 lx max, Direct sun 80,000 lx max, Incandescent 4,000 lx max
- Antistatic electricity: 15kV (non-destructive)
- Drop test: 0.75 m / 2.5 ft drop onto concrete surface
- Protection rate: IP 54

Physical

- Dimensions (w x h x d):
29 x 17 x 34 mm / 1.14 x 0.67 x 1.34 in
- Weight body: Ca. 30 g / 1.06 oz (excl. cable)
- Case: Metal diecast, Black

Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II

Sold separately

- Power supply 100-240V/0.5A, 50/60 Hz, 5V/2A (for RS232)

Models

- Interface versions: RS232, USB

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- | | |
|--|-------------------------------|
| - The Netherlands: Hoofddorp | - Japan: Warabi City |
| - France: Issy Les Moulineaux | - Taiwan: Taipei |
| - Germany: Dietzenbach | - P.R.China: Shanghai |
| - Italy: Villanova di Castenaso (BO) | - Australia: West Ryde |
| - Sweden: Järfälla | |
| - United Kingdom: Luton, Bedfordshire | |
| - U.S.A.: Renton, WA | |
| - Brazil: São Paulo | |

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service