



CG2

UNRIVALLED PERFORMANCE,
CONVENIENCE AND VERSATILITY

FEATURES

- /// Anti-microbial Casing
- /// User Friendly Operation and Maintenance
- /// Printing Resolution of 203 / 305 dpi
- /// RFID Ready and Upgradeable
- /// Prints Labels, Receipts, Tags and Wristbands

APPLICATIONS

- /// Healthcare
- /// General Office
- /// Government
- /// Library
- /// Retail
- /// Transportation and Logistics
- /// Entertainment

TECHNICAL INFORMATION

CG208 / CG212

PRINTING SPECIFICATION		CG208	CG212
Printing Method		Direct Thermal / Thermal Transfer	
Print Resolution, dots/mm (dpi)		8 dots/mm (203dpi)	12 dots/mm (305dpi)
Max. Print Area	Width, mm (inch)	56mm (2.20")	56mm (2.20")
	Length, mm (inch)	600mm (23.60")	400mm (15.75")
Print Speed, mm/sec (ips)		Up to 100mm/sec (4 ips)	
CPU		32 bit RISC	
Printer Memory		Flash ROM: 4MB, RAM: 8MB	

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)			
Sensor Type		I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)	
Media Type		Roll or fan-fold die cut labels, Plain paper face stock, Synthetics and Continuous stock	
Media Thickness		0.06 – 0.19mm (0.002" – 0.007")	
Label Shape	Diameter	Max. outside diameter: Ø 130mm (5.12"), Core diameter: Ø 25.4mm (1") or Ø 38.1mm (1.5")	
	Wind Direction	Face-in/out	
Label Size	Continuous	Width	12 – 60mm (0.47" – 2.36")
		Length	6 – 600mm (0.24" – 23.6")
	Tear-Off	Width	12 – 60mm (0.47" – 2.36")
		Length	12 – 600mm (0.47" – 23.6")
	Cutter	Width	12 – 60mm (0.47" – 2.36")
		Length	22 – 600mm (0.87" – 23.6")
	Dispenser	Width	12 – 60mm (0.47" – 2.36")
		Length	22 – 100mm (0.87" – 3.94")
Ribbon	Size		Width: 59mm (2.32") Max. Length: 100m (328')
	Core Diameter		Ø 12.7mm (0.5")
	Wind Direction		Face-out

FONTS / SYMBOLOGIES		
Fonts	Standard Fonts	Bitmap Fonts Alphanumeric and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)
	Rasterized Fonts	CG Times, CG Triumvirate
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°

COMMUNICATION INTERFACES	
Interface	USB + RS-232C* model, USB + LAN model, Optional: External SATO Wireless LAN**
Command	SBPL (Ver 4.2) SATO Barcode Printer Language

OPERATING CHARACTERISTICS		
Power Requirements		Input voltage adapter: AC100V-240V (auto switching)/40W (peak) – Input voltage printer: 19V/3A
Environment	Operating	0 – 35°C / 30 – 80% RH (without condensation)
	Storage	-10 – 60°C / 15 – 85% RH (without condensation)
Dimension		(W x D x H): 128 x 235 x 173mm (5.04" x 9.25" x 6.81")
Weight		TT model (approx 1.6 kg / 3.5 lbs), DT model (approx 1.5 kg / 3.3 lbs)

MISCELLANEOUS	
Certifications	FCC, UL, CSA, CCC, CE, ROHS compliant, Energy Star™
Anti-microbial Finishing	The material of the casing includes an anti-microbial substance which is tested according to the JISZ2801 standard The anti-microbial casing discourages the growth of bacteria and micro-organisms

OPTIONS	
Accessories	Cutter, Dispenser, RFID HF Kit 13.56Mhz, Wireless LAN (802.11 b/g auto switching), SATO Keypad, Unwinder, SATO Label Gallery™

RFID SPECIFICATION (optional)				
HF	Standard		ISO/IEC 15693	
	Frequency		13,56MHz	
	Transponder	NXP	I-code SLI	112 bytes
		TI	Tag-it HF-I	256 bytes
		Infineon	My-d	992 bytes
RFID Features			Fully integrated HF RFID Reader / Encoder Module, Void marking of damaged or unreadable transponders, RFID data verification after programming. UID reading and printing as text and barcode	

*The RS-232C interface enables connection to PC or SATO Keypad

**Only possible with the USB + RS232-C versions

SATO makes no guarantee that the above features are available in all models, and specifications are liable to change, without notice. Version 09/10. * Measurements are approximate values.



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.


Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health




Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service