

# OPTICON

## Cabled scanners

# OPL6845R

## Barcode laser scanner

RS232

Keyboard Wedge

USB

+ Related products

**OPR2001**

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB
- With auto-trigger stand

**OPR3201**

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB
- With auto-trigger stand

**OPR3001**

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB



### Operating indicators

- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

### Operating keys

- Entry options:
  - 1 scan key

### Communication

- RS232: DB9 PTF connector with external power supply
- Keyboard Wedge: MiniDIN6 F/M connector
- USB: Ver. 1.1, HID/VCP, USB-A connector

### Power

- Voltage requirement: 5V  $\pm$  10% (Keyboard Wedge and USB), 6V (min. 4.5, max. 6.5V) (RS232)
- Current consumption: Max. 250 mA

### Barcode scanner Optics

- Light source: 650 nm visible laser diode
- Scan method: Bi-directional scanning
- Scan rate: 100 scans/sec
- Trigger mode: Manual, auto-trigger, stand detection
- Reading pitch angle: -35 to 0°, 0 to +35°
- Reading skew angle: -50 to -8°, +8 to +50°
- Reading tilt angle: -20 to 0°, 0 to +20°
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. resolution at PCS 0.9: 0.127 mm / 5 mil
- Min. PCS value: 0.45
- Depth of field: At PCS 0.9, Code 39
  - 40 - 500 mm / 1.57 - 19.69 in (1.0 mm / 39 mil),
  - 20 - 350 mm / 0.79 - 13.78 in (0.5 mm / 20 mil),
  - 20 - 200 mm / 0.79 - 7.87 in (0.25 mm / 10 mil),
  - 20 - 100 mm / 0.79 - 3.94 in (0.15 mm / 6 mil),
  - 30 - 70 mm / 1.18 - 2.76 in (0.127 mm / 5 mil)

### Supported Symbolologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/ NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/ Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Composite codes, MicroPDF417, PDF417

### Durability

- Temperature in operation: -5 to 50 °C / -23 to 122 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 5 - 95% (non-condensing)
- Humidity in storage: 5 - 95% (non-condensing)
- Ambient light immunity: Fluorescent 3,000 lx max, Direct sun 50,000 lx max, Incandescent 3,000 lx max
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Vibration test: 10 - 100 Hz with 2G for 1 hour
- Protection rate: IP 42

### Physical

- Dimensions (w x h x d):
  - 57 x 159 x 32 mm / 2.24 x 6.26 x 1.26 in
- Dimensions stand (w x h x d):
  - 160 x 190 x 245 mm / 6.29 x 7.48 x 9.64 in (excl. scanner)
- Weight body: Ca. 90 g / 3.2 oz (excl. cable)
- Weight stand: Ca. 290 g / 10.2 oz
- Case: ABS, Black or White

### Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II

### Enclosed items

- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A (for RS232)
- Stand (optionally sold separately)

### Models

- Interface versions: RS232, Keyboard Wedge, USB
- Color versions: Black, White
- Package versions: Stand included, Scanner only

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

• **The Netherlands:** Hoofddorp  
• **France:** Issy Les Moulineaux  
• **Germany:** Dietzenbach  
• **Italy:** Castel Maggiore (BO)  
• **Spain:** Valencia  
• **Sweden:** Järfälla  
• **United Kingdom:** Luton, Bedfordshire  
• **U.S.A.:** Renton, WA  
• **Japan:** Warabi City

• **Taiwan:** Taipei  
• **P.R.China:** Shanghai  
• **Australia:** Kariang  
• **Brazil:** São Paulo

Opticon Sensors Europe B.V  
European headquarters  
Opaallaan 35  
2132 XV Hoofddorp  
The Netherlands  
phone: +31 (0)23-5692700  
fax: +31 (0)23-5638266  
email: sales@opticon.com  
internet: www.opticon.com

**OPTICON**  
WWW.OPTICON.COM



[www.logiscenter.com](http://www.logiscenter.com)  
902 050 030



[www.logiscenter.it](http://www.logiscenter.it)  
02 479 216 97



[www.logiscenter.de](http://www.logiscenter.de)  
info@logiscenter.de



[www.logiscenter.pt](http://www.logiscenter.pt)  
308 800 842

## About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permanent stock of more than 12,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.


**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.

## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health




Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables  
(labels, ribbons, PVC cards)

## Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands  
Technical Service